imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



VARIOFACE module, with push-in connection and D-SUB miniature socket strip, for mounting on NS 35 rails, 9-pos.

The illustration shows a 15 position version with male D-sub connector.

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 796538
GTIN	4046356796538

Technical data

Dimensions

Width	36.8 mm
Height	72.1 mm
Depth	46.6 mm

Ambient conditions

Ambient temperature (operation)	-20 °C 50 °C
Ambient temperature (storage/transport)	-20 °C 70 °C

General

Max. perm. operating voltage	25 V AC	
	60 V DC	
Max. perm. current (per branch)	2 A	
Number of positions	9	
Status display	No	
Mounting position	any	

Connection data for connection 1

Connection name	Field level
-----------------	-------------



Technical data

Connection data for connection 1

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section solid	0.14 mm ² 2.5 mm ²
Conductor cross section flexible	0.14 mm ² 2.5 mm ²
Conductor cross section AWG	26 14

Connection data for connection 2

Connection name	Controller level
Connection method	D-SUB socket strip
Number of connections	1
Number of positions	9

Standards and Regulations


Connection in acc. with standard	CSA
Standards/regulations	IEC 60664
	DIN EN 50178
Rated surge voltage	1.2 kV
Degree of pollution	2
Overvoltage category	11

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Circuit diagram



Approvals

Approvals

Approvals

 $\mathsf{CSA} \ / \ \mathsf{UL} \ \mathsf{Recognized} \ / \ \mathsf{cUL} \ \mathsf{Recognized} \ / \ \mathsf{EAC} \ / \ \mathsf{CSAus} \ / \ \mathsf{cCSAus}$



Approvals

Ex Approvals

Г

Γ

Γ

Approval details

CSA	()	http://www.csagroup.org/services-industries/product-listing/ 2122203		2122203
Nominal voltage UN			105 V	
Nominal current IN			2 A	
mm²/AWG/kcmil			26-14	

UL Recognized	http://database.ul.com	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 2387	
Nominal voltage UN		125 V	
Nominal current IN		2 A	
mm²/AWG/kcmil		26-14	

cUL Recognized	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 238705
Nominal voltage UN	125 V
Nominal current IN	2 A
mm²/AWG/kcmil	26-14

EAC	EAC			RU C- DE.A*30.B.01742
CSAus	€ US	http://www.csagroup.org/services-industries/product-listing/		2122203
Nominal voltage UN			105 V	
Nominal current IN			2 A	
mm²/AWG/kcmil			28-14	

08/18/2018 Page 3 / 4

٦



Approvals

cCSAus

http://www.c

http://www.csagroup.org/services-industries/product-listing/

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com