

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The figure shows the 37-pos. version with D-SUB plug.

VARIOFACE module, with push-in connections and D-SUB 50 socket connector, for mounting on NS 35 rails



## **Key Commercial Data**

| Packing unit | 1 STK           |
|--------------|-----------------|
| GTIN         | 4 046356 796606 |
| GTIN         | 4046356796606   |

### Technical data

#### **Dimensions**

| Width  | 97.7 mm |
|--------|---------|
| Height | 75.8 mm |
| Depth  | 63 mm   |

#### Ambient conditions

| Ambient temperature (operation)         | -20 °C 50 °C |
|---|--------------|
| Ambient temperature (storage/transport) | -20 °C 70 °C |

#### General

| Max. perm. operating voltage    | 25 V AC |
|---------------------------------|---------|
|                                 | 60 V DC |
| Max. perm. current (per branch) | 1 A     |
| Number of positions             | 50      |
| Status display                  | No      |
| Mounting position               | any     |

### Connection data for connection 1

| Connection name | Field level |
|-----------------|-------------|
|-----------------|-------------|



## Technical data

### Connection data for connection 1

| Connection method                | Push-in connection |
|----------------------------------|--------------------|
| Stripping length                 | 8 mm               |
| Conductor cross section solid    | 0.14 mm² 2.5 mm²   |
| Conductor cross section flexible | 0.14 mm² 2.5 mm²   |
| Conductor cross section AWG      | 26 14              |

#### Connection data for connection 2

| Connection name       | Controller level   |
|-----------------------|--------------------|
| Connection method     | D-SUB socket strip |
| Number of connections | 1                  |
| Number of positions   | 50                 |

### Standards and Regulations


| Connection in acc. with standard | CSA          |
|----------------------------------|--------------|
| Standards/regulations            | IEC 60664    |
|                                  | DIN EN 50178 |
| Rated surge voltage              | 1.2 kV       |
| Degree of pollution              | 2            |
| Overvoltage category             | II           |

### **Environmental Product Compliance**

| China RoHS | Environmentally Friendly Use Period = 50  |  |
|------------|---|--|
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |  |

# Drawings

## Circuit diagram



# Approvals

#### Approvals

#### Approvals

CSA / UL Recognized / cUL Recognized / EAC / CSAus / cULus Recognized



# Approvals

Ex Approvals

### Approval details

| CSA                | <b>(F</b> | http://www.csagroup.org/services-industries/product-listing/ |       | 2122203 |
|--------------------|-----------|--|-------|---------|
|                    |           |  |       |         |
| Nominal voltage UN |           |  | 105 V |         |
| Nominal current IN |           |  | 1 A   |         |
| mm²/AWG/kcmil      |           |  | 26-14 |         |

| UL Recognized      | <i>7</i> .12 | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm |       | FILE E 238705 |
|--------------------|--------------|---|-------|---------------|
|                    |              |   |       |               |
| Nominal voltage UN |              |   | 125 V |               |
| Nominal current IN |              |   | 1 A   |               |
| mm²/AWG/kcmil      |              |   | 26-14 |               |

| cUL Recognized     | c <b>A1</b> | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm |       | FILE E 238705 |
|--------------------|-------------|---|-------|---------------|
|                    |             |   |       |               |
| Nominal voltage UN |             |   | 125 V |               |
| Nominal current IN |             |   | 1 A   |               |
| mm²/AWG/kcmil      |             |   | 26-14 |               |

EAC RU C-DE.A\*30.B.01742

| CSAus              | <b>∰</b> ° | http://www.csagroup.org/services-industries/product-listing/ |       | 2122203 |
|--------------------|------------|--|-------|---------|
|                    |            |  |       |         |
| Nominal voltage UN |            |  | 105 V |         |
| Nominal current IN |            |  | 1 A   |         |
| mm²/AWG/kcmil      |            |  | 28-14 |         |



## Approvals

cULus Recognized



http://www.csagroup.org/services-industries/product-listing/

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com