



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Cable - CABLE-KS50/KS50/17M/YUC/CS - 2904418

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled round cable with two molded 50-pos. socket strips (1:1 connection). Cable length: 17.0 m



### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 STK    |
| Custom tariff number | 85444290 |
| Country of origin    | China    |

### Technical data

#### General

|   |   |
|---|---|
| Nominal voltage $U_N$                         | 30 V DC                                 |
| Max. current carrying capacity per path       | 500 mA (up to 70°C ambient temperature) |
| Max. conductor resistance                     | 0.16 $\Omega$ /m                        |
| Length of cable                               | 17 m                                    |
| Single wire, cross section                    | 0.14 mm <sup>2</sup>                    |
| Single wire, cross section [AWG]              | 26                                      |
| Conductor construction: Number of litz wires: | 7                                       |
| Single wire, material                         | Cu tin-plated                           |
| External diameter                             | 11 mm                                   |
| Shielding                                     | yes                                     |
| Outer sheath, material                        | PVC                                     |
| External sheath, color                        | gray RAL 7035                           |

#### Environmental conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

## Cable - CABLE-KS50/KS50/17M/YUC/CS - 2904418

### Technical data

#### Environmental conditions

|                     |                                    |
|---------------------|------------------------------------|
| Flame resistance    | IEC 60332-3-22                     |
| Resistance to oil   | DIN VDE 0472 Part 803, test type B |
| Gasoline resistance | Against occasional splashes        |

#### Connector, module side

|                       |                           |
|-----------------------|---------------------------|
| Connection name       | Field level               |
| Connection method     | Yokogawa, KS compatible   |
| Torque                | 0.5 Nm (Screw connection) |
| Number of connections | 1                         |
| Number of positions   | 50                        |

#### Connector, controller side

|                       |                                |
|-----------------------|--------------------------------|
| Connection name       | Controller level               |
| Connection method     | Yokogawa, I/O cards compatible |
| Torque                | 0.5 Nm (Screw connection)      |
| Number of connections | 1                              |
| Number of positions   | 50                             |

#### Supported controller

|                     |                          |
|---------------------|--------------------------|
| Controller          | YOKOGAWA CS3000 CentumVP |
| - suitable I/O card | AAR145                   |

#### Standards and Regulations

|                   |                                    |
|-------------------|------------------------------------|
| Resistance to oil | DIN VDE 0472 Part 803, test type B |
| Flame resistance  | IEC 60332-3-22                     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 6.0 | 27249205 |
| eCl@ss 7.0 | 27249205 |
| eCl@ss 8.0 | 27249205 |
| eCl@ss 9.0 | 27242220 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000237 |
| ETIM 3.0 | EC000237 |

## Cable - CABLE-KS50/KS50/17M/YUC/CS - 2904418

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC000237 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 26121620 |
| UNSPSC 7.0901 | 26121620 |
| UNSPSC 11     | 26121620 |
| UNSPSC 12.01  | 26121620 |
| UNSPSC 13.2   | 26121620 |