



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Antenna - RAD-900-ANT-OMNI-2-2-RSMA - 2904801

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Omnidirectional antenna, 900 MHz, gain: 2 dBi, polarization: linear, degree of protection: IP65, connection: RSMA (male), incl. 1.8 m / 6 ft. connecting cable and mounting bracket for wall mounting

Why buy this product

- For freely mobile applications
- For multipoint or mesh connections

Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4046356902113

Technical data

Dimensions

Width	0.3 cm
Height	8.9 cm

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 75 °C

General

With connecting cable	yes
Frequency range	900 MHz
	900 MHz
Horizontal beamwidth	360 °
Vertical beamwidth	N/A
Polarization	Linear vertical
Impedance	50 Ω

Antenna - RAD-900-ANT-OMNI-2-2-RSMA - 2904801

Technical data

General


Gain	2.15 dBi
Connection method	RSMA (male)
Material	V2A (Antenna housing)
	V2A (Bracket)
Mounting type	Wall mounting

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Schematic diagram



Schematic diagram



Installation example