imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



VARIOFACE Professional (VIP) board for the ROC800 controller

Product Features

- These system-specific interface modules for the ROC800 controller are used in combination with the relevant system cables
- Interface from field wiring to ROC800 controller
- Compact design reduces space requirements in the control cabinet
- Field side I/O marking clearly identified when device is mounted.
- Integrated ZB marker provides per-channel labeling
- Rugged metal mounting foot allows easy DIN rail installation and removal.



Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|---------------|
| Weight per Piece (excluding packing) | 100.0 g |
| Country of origin | United States |

Technical data

Dimensions

| Width | 36.8 mm |
|--------|---------|
| Height | 72.1 mm |
| Depth | 46.6 mm |

Ambient conditions

| Ambient temperature (operation) | -20 °C 50 °C |
|---|--------------|
| Ambient temperature (storage/transport) | -20 °C 70 °C |

General



Technical data

General

| Max. perm. operating voltage | 60 V AC/DC |
|---------------------------------|--------------|
| Max. perm. current (per branch) | 1 A |
| Number of positions | 10 |
| Status display | No |
| Mounting position | any |
| Standards/regulations | IEC 60664 |
| | DIN EN 50178 |
| | IEC 62103 |
| Degree of pollution | 2 |
| Overvoltage category | Ш |

Connection data for connection 1

| Connection name | Field level |
|----------------------------------|--|
| Connection in acc. with standard | IEC / EN |
| Connection method | Push-in connection |
| Stripping length | 8 mm |
| Conductor cross section solid | 0.14 mm ² 2.5 mm ² |
| Conductor cross section flexible | 0.14 mm ² 2.5 mm ² |
| Conductor cross section AWG | 26 14 |
| Number of positions | 10 |

Connection data for connection 2

| Connection name | Controller level |
|-----------------------|-----------------------------|
| Connection method | IDC/FLK pin strip (2.54 mm) |
| Number of connections | 1 |
| Number of positions | 10 |
| Pitch | 2.54 mm |

Supported controller

| Controller | Emerson ROC800 |
|---------------------|----------------|
| - suitable I/O card | ROC800 AI-16 |

Standards and Regulations

| Standards/regulations | IEC 60664 |
|-----------------------|--------------|
| | DIN EN 50178 |
| | IEC 62103 |
| Degree of pollution | 2 |
| Overvoltage category | Ш |



Classifications

eCl@ss

| eCl@ss 4.0 | 27250313 |
|------------|----------|
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27250313 |
| eCl@ss 6.0 | 27242608 |
| eCl@ss 7.0 | 27141152 |
| eCl@ss 8.0 | 27141152 |
| eCl@ss 9.0 | 27141152 |

ETIM

| ETIM 2.0 | EC001434 |
|----------|----------|
| ETIM 3.0 | EC001604 |
| ETIM 4.0 | EC001604 |
| ETIM 5.0 | EC002780 |

UNSPSC

| UNSPSC 6.01 | 30211824 |
|---------------|----------|
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11 | 39121421 |
| UNSPSC 12.01 | 39121421 |
| UNSPSC 13.2 | 39121421 |

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details



Approvals

Γ

| mm²/AWG/kcmil | 26-14 |
|--------------------|-------|
| Nominal current IN | 1 A |
| Nominal voltage UN | 60 V |

| mm²/AWG/kcmil | 26-14 |
|--------------------|-------|
| Nominal current IN | 1 A |
| Nominal voltage UN | 60 V |

cULus Recognized

Accessories

Accessories

System cable

Cable - VIP-CAB-FLK10/0,14/0,5M - 2318305



Assembled round cable with two molded 10-pos. socket strips (1:1 connection). The cable has a 90° punched on connector and a 180° punched on connector, cable length: 0.5 m

Cable - VIP-CAB-FLK10/0,14/1,0M - 2318318



Assembled round cable with two molded 10-pos. socket strips (1:1 connection). The cable has a 90° punched on connector and a 180° punched on connector, cable length: 1 m



Accessories

Cable - VIP-CAB-FLK10/0,14/1,5M - 2318321



Assembled round cable with two molded 10-pos. socket strips (1:1 connection). The cable has a 90° punched on connector and a 180° punched on connector, cable length: 1.5 m

Cable - VIP-CAB-FLK10/0,14/2,0M - 2318334



Assembled round cable with two molded 10-pos. socket strips (1:1 connection). The cable has a 90° punched on connector and a 180° punched on connector, cable length: 2 m

Cable - VIP-CAB-FLK10/0,14/3,0M - 2318347



Assembled round cable with two molded 10-pos. socket strips (1:1 connection). The cable has a 90° punched on connector and a 180° punched on connector, cable length: 3 m

Cable - VIP-CAB-FLK10/0,14/4,0M - 2318350



Assembled round cable with two molded 10-pos. socket strips (1:1 connection). The cable has a 90° punched on connector and a 180° punched on connector, cable length: 4 m

Cable - VIP-CAB-FLK10/0,14/6,0M - 2318363



Assembled round cable with two molded 10-pos. socket strips (1:1 connection). The cable has a 90° punched on connector and a 180° punched on connector, cable length: 6 m

Required add-on products

05/23/2016 Page 5 / 6



Accessories


Front adapters - FLKM 10-PA-ROC800 - 2904889



VARIOFACE front adapters for ROC800 controller

Drawings





Connection scheme VIP-2/.../FLK50 (1-40) /S7

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com