



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Monitor - VL FPM 15 - 2913017

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



15-in. display shown

Key commercial data

Packing unit	0
Minimum order quantity	1
GTIN	 4 046356 662260
Custom tariff number	85285100
Country of origin	TAIWAN

Technical data

Display data

Display	38.1 cm/15" TFT active
Resolution	1024 x 768 Pixel (XGA)
Backlighting	CCFL
Display backlight MTBF	> 50000 h
Touch screen	Resistive industrial touch screen
Colors	16.2 million

Computer data

Processor	without
Main memory	without
Processor fan	Without fan
Data memory	without
Interfaces	1x DVI-D, 1x VGA, 2x USB
Network	without
Operating systems	No operating system
Slots	without
Power supply unit	24 V DC +/- 20%

General data

Installation dimension, width	386.6 mm
Installation dimension, height	285 mm

Monitor - VL FPM 15 - 2913017

Technical data

General data

Note regarding installation dimension	Panel cutout
Mounting type	Panel cutout or VESA mount
Weight	4.51 kg

Ambient Conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Classifications

eclass

eCl@ss 5.1	27242301
eCl@ss 6.0	27242301
eCl@ss 7.0	27242301

etim

ETIM 4.0	EC001413
----------	----------