

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Housing upper part, complete with COMBICON headers and screw connectors for full mounting of components. 12-pos., housing width: 17.5 mm



The illustration shows the green product version

Product Features

- ▼ Tool-free mounting
- Gold contacts for data transmission and power supply (125 V, 8 A)
- When a device is unplugged from the system as a whole, the signal chain is not interrupted# Supply via standard MINI COMBICON plug
- ✓ Large assembly area
- ME...TBUS connector with 5 parallel contacts can be snapped onto DIN rails to save space
- Recessed labeling areas
- ✓ Inflammability class V0 according to UL 94
- Fast mounting on DIN rails according to EN 60715
- Material and part identification embossed on the housing (recyclability)
- Cost savings thanks to easy device production
- Optional BUS connection integrated in the housing, for either parallel or serial contacting
- Functional earth ground contact (EMC) integrated in the housing base
- Metal foot catch
- ☑ Electronic components can be partially removed.



Key commercial data

Packing unit	11
Weight per Piece (excluding packing)	42.7 GRM
Custom tariff number	85369010
Country of origin	Germany



Technical data

General

Housing type	Component housing
Housing material	Polyamide
Color	light gray

Dimensions

Constructional height	38.5 mm
Width	17.5 mm

Technical data

Connection in acc. with standard	CUL
Nominal voltage U _N	300 V
Nominal current I _N	12 A
AWG/kcmil	30-12
Indicator1	CUL1
Inflammability class according to UL 94	V0
Number of positions	12
	36
	24

Articles in set

Electronic housing - ME 17,5 OT-MSTBO KMGY - 2853747



Upper part of housing, for COMBICON connection, double-level

Base strip - MSTBO 2,5/ 3-G1L KMGY - 2853750



Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Assembly: Soldering



Articles in set

Base strip - MSTBO 2,5/ 3-G1R KMGY - 2853763



Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Assembly: Soldering

Printed-circuit board connector - MSTBT 2,5/ 3-ST KMGY - 1971947



Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Connection method: Screw connection, Color: Light gray, Contact surface: Tin

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC000886

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501





Approvals Approvals Approvals UL Recognized / cUL Recognized / cULus Recognized Ex Approvals Approvals submitted Approval details UL Recognized **\$\)** cUL Recognized **51** D В mm²/AWG/kcmil 30-12 30-12 Nominal current IN 12 A 10 A Nominal voltage UN 250 V 300 V cULus Recognized • Sus

Drawings





Schematic diagram





Schematic diagram





Pin assignment left

Pin assignment right

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com