

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Stewart Connector 11118 Susquehanna Trail South Glen Rock, PA 17327 Phone: (717) 235-7512 Fax: (717) 235-7954

Stewart Pneumatic Crimp Tool



Part Number: 2940252-01 – Crimp tool only, die sets sold separately

Features:

- Uses standard interchangeable Stewart production die sets
- High strength aluminum alloy construction gives the machine an excellent strength to weight ratio
- Anodized finish for durability
- Actuated with foot pedal
- Simple design for trouble-free operation
- Oil impregnated bronze bearings, used on all pivoting points, to eliminate the need for lubrication
- Small footprint allows the machine to be used where bench space is at a premium
- Visor style guard around die set for safety, remains attached to machine preventing loss of guard, yet allows for quick easy access to die
- Die set is retained with a thumb screw, which is accessible from the operator side without turning the machine upside down, or on its side

Specifications:

Air Supply: 60 - 150 PSI

Output Force: 1448 Lbs @ 80 PSI

Weight: 5 Lbs

Dimensions: $4\frac{1}{2}$ " wide x $8\frac{1}{4}$ " long x 5" high