

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









EMG150-LG

Order No.: 2946023



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2946023

Electronic housing, for PCB insertion, without screw connection terminal blocks and cover

Commercial data	
GTIN (EAN)	4 017918 081997
sales group	F001
Pack	2 pcs.
Customs tariff	85472000
Catalog page information	Page 549 (CC-2009)

Product notes

WEEE/RoHS-compliant since: 04/04/2005



http://

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Housing type	Component housing
Housing material	Polycarbonate fiber reinforced
Color	green

Length	75 mm
Width	150 mm
Number of positions	58
Pitch	5 mm

Technical data

Ambient temperature (operation)	-40 °C 125 °C
Inflammability class acc. to UL 94	V0
Power dissipation at 20°C in the horizontal mounting position	12.3 W 13.1 W 7.5 mm
	13.1 W 13.8 W 15 mm
	13.6 W 14.9 W 52 mm

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm

Accessories

Item

Designation

Assembly		
2941510	EMG-KA	Terminal block/screw cover, set consisting of 50 strips each for terminal blocks and screw openings, 1 strip covers 12 terminal points.
2941510	EMG-KA	Terminal block/screw cover, set consisting of 50 strips each for terminal blocks and screw openings, 1 strip covers 12 terminal

points.

Description

General

2947035

2946049	P 1-EMG150	PCB for assembling electronic components
Marking		
2947035	EMG-GKS 12	Equipment marker, width 12 mm

Equipment marker, width 12 mm

EMG-GKS 12


2941594	EMG-GKS 22	Equipment marker tag, width 22 mm
2941594	EMG-GKS 22	Equipment marker tag, width 22 mm

Additional products


Item	Designation	Description	
Assembly	Assembly		
2943178	EMG150-H 7,5MM KLAR	Covering hood, for the contact and dust-protected encapsulation of the components, in transparent design. Height: 7.5 mm	
2943165	EMG150-H 15MM KLAR	Covering hood, for the contact and dust-protected encapsulation of the components, in transparent design. Height: 15 mm, width: 150 mm	
2943521	EMG150-H 52MM GN	Covering hood, for the contact and dust-protected encapsulation of the components, in green design. Height: 52 mm, width: 150 mm	

Diagrams/Drawings

Dimensioned drawing



1 = Top edge of the PCB B = Housing width



Pitch 5 mm

a = Area for mounting components, 38 mm in the hood

b = Area for mounting components, 45 mm in the housing

Address

PHOENIX CONTACT Deutschland GmbH Flachsmarktstr. 8 32825 Blomberg,Germany Phone +49 5235 3 12000 Fax +49 5235 3 41200 http://www.phoenixcontact.de



© 2011 Phoenix Contact Technical modifications reserved;