imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



TP 15T

Order No.: 2985204

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2985204

Touch panel with 15.1" graphics-capable TFT display, 256 colors x 1024 X 768 pixels, 1x Ethernet, 2x USB and integrated runtime of the Visu+ visualization software.

Commercial data

GTIN (EAN)	4 046356 117197
sales group	K310
Pack	1 pcs.
Customs tariff	84714100
Catalog page information	Page 135 (AX-2009)

Product notes

WEEE/RoHS-compliant since: 05/11/2010



http://

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Display data

Display	38.1 cm/15" TFT active
Resolution	1024 x 768 Pixel
Touch screen	Resistive industrial touch screen
Colors	256 colors



catalog



Computer data

Processor	Xscale PXA320, 806 MHz
Main memory	128 MByte SDRAM
Data memory	256 Mbyte external Compact Flash card for applications
Interfaces	10/100 MBit Ethernet; 2 x USB Host 1.1
Operating systems	Windows CE 5.0

General data

External dimension, width	400 mm
External dimension, height	329 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	373 mm
Installation dimension, height	302 mm
Mounting type	Installation in front plate

Ambient Conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C 50 °C
Ambient temperature (storage/transport)	-25 °C 70 °C
Permissible humidity (operation)	20 % 85 % (no condensation)
Permissible humidity (storage/transport)	10 % 95 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Certificates / Approvals

(GL)

Certification

ABS, BV, CUL Listed, GL, UL Listed

Address

PHOENIX CONTACT Deutschland GmbH Flachsmarktstr. 8 32825 Blomberg,Germany Phone +49 5235 3 12000 Fax +49 5235 3 41200 http://www.phoenixcontact.de



© 2011 Phoenix Contact Technical modifications reserved;