

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Slave protocol chip - IBS SUPI 4 TQFP - 2988117

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Slave protocol chip, for INTERBUS





Key Commercial Data

| Packing unit | 160 STK |
|------------------------|-----------------|
| Minimum order quantity | 160 STK |
| GTIN | 4 046356 341752 |
| GTIN | 4046356341752 |

Technical data

Dimensions

| Width | 10 mm |
|--------|-------|
| Height | 1 mm |
| Depth | 10 mm |
| Length | 10 mm |

Ambient conditions

| Ambient temperature (storage/transport) | -65 °C 150 °C (at max. 60 %) |
|---|--|
| Ambient temperature (operation) | -40 °C 85 °C (at max. 75% humidity during operation) |

Module

| IC power supply voltage | 3.3 V DC ±10 % (DC) |
|-----------------------------|--|
| Typical current consumption | 20 mA |
| Connection method | Remote bus, local bus or installation remote bus |
| Interface | INTERBUS |
| Internal data length | 64 bytes IN/64 bytes OUT |
| User interface | MFP interface, digital I/O (16 IN/16 OUT, 32 IN, 32 OUT), parallel and serial port for microprocessors |

General



Slave protocol chip - IBS SUPI 4 TQFP - 2988117

Technical data

General

| Туре | TQFP 64 |
|----------------------------------|---|
| Environmental Product Compliance | |
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com