



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Media module - FL SFP GT - 2989420

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Gigabit SFP module for transmission up to 100 m.

Product Description

SFP module with a data transmission speed of 1000 Mbps and a maximum transmission length of 100 m.



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4046356346122

Technical data

Dimensions

Width	13.7 mm
Height	8.95 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (non-condensing)
Ambient temperature (storage/transport)	-40 °C ... 85 °C (non-condensing)

Interfaces

Interface 1	Ethernet (RJ45)
No. of ports	1 (RJ45 port)
Transmission physics	Copper
Transmission speed	1 Gbps
Transmission length	100 m (per segment)
Signal LEDs	depending on the Factoryline device

Function

Basic functions	SFP module as copper port
-----------------	---------------------------

Media module - FL SFP GT - 2989420

Technical data

Function

Status and diagnostic indicators	via a Factoryline device
----------------------------------	--------------------------

Network expansion parameters

Maximum conductor length (twisted pair)	100 m
-----------------------------------------	-------

Supply voltage

Supply voltage	3.3 V (via Factoryline switch)
Max. current consumption	375 mA
Current consumption	375 mA

General

Mounting type	Insert in SFP slot
Type AX	Factoryline devices with SFP slot
Net weight	33.4 g
Housing material	Metal

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>