

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







2N2223 2N2223A

SILICON DUAL NPN TRANSISTORS




www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N2223 and 2N2223A are dual silicon NPN transistors manufactured by the epitaxial planar process utilizing two individual chips mounted in a hermetically sealed metal case designed for differential amplifier applications.

MARKING: FULL PART NUMBER



MAXIMUM RA	ATINGS: (T _A =25°C)	SYMBOL		UNITS
Collector-Bas	e Voltage	V_{CBO}	100	V
Collector-Emi	tter Voltage	VCER	80	V
Collector-Emi	tter Voltage	VCEO	60	V
Emitter-Base	Voltage	VEBO	7.0	V
Continuous C	ollector Current	IC	500	mA
Power Dissipa	ation (One Die)	P_{D}	500	mW
Power Dissipa	ation (Both Dice)	P_{D}^{-}	600	mW
Operating and	d Storage Junction Temperature	T _J , T _{stg}	-65 to +200	°C
ELECTRICAL	_ CHARACTERISTICS PER TRAI	NSISTOR: (T _A =25°C	unless otherwise noted	d)
SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I _{CBO}	V _{CB} =80V		10	nA
I _{CBO}	V _{CB} =80V, T _A =150°C		15	μΑ
IEDO	V=n=5.0V		10	nΔ

SYMBOL	TEST CONDITIONS	MIN ^	MAX	UNITS
I _{CBO}	V _{CB} =80V		10	nA
ICBO	V _{CB} =80V, T _A =150°C		15	μΑ
I _{EBO}	V _{EB} =5.0V		10	nA
BV _{CBO}	I _C =100μA	100		V
BVCER	I_C =100mA, R_{EB} =10 Ω	80		V
BVCEO	I _C =30mA	60		V
BVEBO	I _E =100μA	7.0		V
VCE(SAT)	I _C =50mA, I _B =5.0mA		1.2	V
V _{BE} (SAT)	I_C =50mA, I_B =5.0mA		0.9	V
h _{FE}	V _{CE} =5.0V, I _C =10μA	15		
h _{FE}	V _{CE} =5.0V, I _C =100μA	25	150	
h _{FE}	V_{CE} =5.0V, I_{C} =10mA	50	200	
f _T	V _{CE} =10V, I _C =50mA, f=20MHz	50		MHz
C _{ob}	V _{CB} =10V, I _E =0, f=1.0MHz		15	pF
C _{ib}	V_{BE} =0.5V, I_{C} =0, f=1.0MHz		85	pF
h _{ib}	V_{CB} =5.0V, I_{C} =1.0mA, f=1.0kHz	20	30	Ω
h _{rb}	V _{CB} =5.0V, I _C =1.0mA, f=1.0kHz		3.0	x10 ⁻⁴
h _{fe}	V_{CE} =5.0V, I_{C} =1.0mA, f=1.0kHz	40	200	
h _{ob}	V_{CB} =5.0V, I_{C} =1.0mA, f=1.0kHz		0.5	μS

OD CD	, 0					
MATCHING CHARA	CTERISTICS:	2N2	2223	2N2:	223A	UNITS
SYMBOL	TEST CONDITIONS	MIN	MAX	MIN	MAX	
h _{FE1} /h _{FE2} (Note 1)	V_{CE} =5.0V, I_{C} =100 μ A	8.0	1.0	0.9	1.0	
$ V_{BE1}-V_{BE2} $	V_{CE} =5.0V, I_{C} =100 μ A	-	15	-	5.0	mV

Notes: (1) The lowest reading is taken as $h_{\mbox{\scriptsize FE1}}$.


R0 (22-January 2014)

2N2223 2N2223A

SILICON DUAL NPN TRANSISTORS




TO-78 CASE - MECHANICAL OUTLINE



A (DIA) 0.335 0.370 8.51 9.40 B (DIA) 0.305 0.335 7.75 8.51 C 0.150 0.185 3.81 4.70 D - 0.040 - 1.02 E 0.500 - 12.70 - F (DIA) 0.016 0.021 0.41 0.53	DIMENSIONS					
A (DIA) 0.335 0.370 8.51 9.40 B (DIA) 0.305 0.335 7.75 8.51 C 0.150 0.185 3.81 4.70 D - 0.040 - 1.02 E 0.500 - 12.70 - F (DIA) 0.016 0.021 0.41 0.53		INCHES		MILLIM	MILLIMETERS	
B (DIA) 0.305 0.335 7.75 8.51 C 0.150 0.185 3.81 4.70 D - 0.040 - 1.02 E 0.500 - 12.70 - F (DIA) 0.016 0.021 0.41 0.53	SYMBOL	MIN	MAX	MIN	MAX	
C 0.150 0.185 3.81 4.70 D - 0.040 - 1.02 E 0.500 - 12.70 - F (DIA) 0.016 0.021 0.41 0.53	A (DIA)	0.335	0.370	8.51	9.40	
D - 0.040 - 1.02 E 0.500 - 12.70 - F (DIA) 0.016 0.021 0.41 0.53	B (DIA)	0.305 0.335		7.75	8.51	
E 0.500 - 12.70 - F (DIA) 0.016 0.021 0.41 0.53	С	0.150 0.185		3.81	4.70	
F (DIA) 0.016 0.021 0.41 0.53	D	-	0.040	-	1.02	
 	E	0.500 -		12.70	-	
G 0.200 5.08	F (DIA)	0.016	0.021	0.41	0.53	
0.200 0.00	G	0.200		5.	08	
H 0.100 2.54	Н	0.100		2.54		
J 0.028 0.034 0.71 0.86	J	0.028	0.034	0.71	0.86	
K 0.029 0.045 0.74 1.14	K	0.029	0.045	0.74	1.14	

TO-78 (REV: R1)



MARKING: FULL PART NUMBER

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- · Special wafer diffusions
- · PbSn plating options
- Package details
- · Application notes
- · Application and design sample kits
- · Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110

Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (000)



Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

Summary: All transistors manufactured in the TO-78 package are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement
CEN876	N/A
CEN894	N/A
CEN895	N/A
CEN896	N/A
CEN911	N/A
CEN947	N/A
CEN955 W/DATA	N/A
MD2219A	N/A
MD2369	N/A
MD2369A	N/A
MD2369B	N/A
MD2905	N/A
MD2905A	N/A
MD5179	N/A
MD7000	N/A
MD7001	N/A
MD7003	N/A
MD7003A	N/A
MD7003B	N/A
MD8002	N/A
MD8003	N/A
MD918	N/A
MD918A	N/A
MD918B	N/A
MD984	N/A
2N2060	N/A
2N2060A	N/A
2N2060M	N/A
2N2223	N/A
2N2223A	N/A
2N2453	N/A
2N2453A	N/A
2N2480	N/A
2N2480A	N/A
2N2639	N/A
2N2640	N/A
2N2641	N/A
2N2642	N/A
*** CONTINUED ***	

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

*** CONTINUED FROM PRIOR PAGE ***

Central Part Number	Donlogomont
2N2643	Replacement N/A
2N2644	N/A
2N2652	N/A
2N2652A	N/A
2N2720	N/A N/A
2N2720 2N2721	N/A N/A
2N2721 2N2722	N/A
2N2903	N/A
2N2903A	N/A
2N2913	N/A
2N2914	N/A
2N2915	N/A
2N2915A	N/A
2N2916	N/A
2N2916A	N/A
2N2917	N/A
2N2918	N/A
2N2919	N/A
2N2919A	N/A
2N2920	N/A
2N2920A	N/A
2N3726	N/A
2N3727	N/A
2N3806	N/A
2N3807	N/A
2N3808	N/A
2N3809	N/A
2N3810	N/A
2N3810A	N/A
2N3811	N/A
2N3811A	N/A
2N4015	N/A
2N4016	N/A
2N4854	N/A
2N4937	N/A
2N4938	N/A
2N4939	N/A
2N5793	N/A
2N5794	N/A
2N5796	N/A
2N5912	N/A
2N6502	N/A

*** CONTINUED ***

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

*** CONTINUED FROM PRIOR PAGE ***

Central Part Number	Replacement
Central would be happy to assist yo	ou by providing additional information or technical data to help locate an alternate source if we
have no replacement available. Plea	ase email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002