imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





DUAL SILICON NPN TRANSISTOR

TO-78 CASE



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N2918 is a Dual Silicon NPN Transistor utilizing two individual chips mounted in a hermetically sealed metal case designed for differential amplifier applications.

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
Collector-Base Voltage	VCBO	45	V
Collector-Emitter Voltage	VCEO	45	V
Emitter-Base Voltage	V _{EBO}	6.0	V
Continuous Collector Current	IC	30	mA
Power Dissipation (One Die)	PD	300	mW
Power Dissipation (Both Dice)	PD	500	mW
Power Dissipation (One Die, T _C =25°C)	PD	750	mW
Power Dissipation (Both Dice, T _C =25°C)	PD	1.5	W
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +200	°C


ELECTRICAL	CHARACTERISTICS: (TA=25°C unless otherwise	e noted)		
SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
ICBO	V _{CB} =45V		10	nA
ICEO	V _{CE} =5.0V		2.0	nA
IEBO	V _{EB} =5.0V		2.0	nA
BVCBO	Ι _C =10μΑ	45		V
BVCEO	I _C =10mA	45		V
BVEBO	I _F =10μA	6.0		V
V _{CE(SAT)}	I _C =1.0mA, I _B =0.1mA		0.35	V
V _{BE(ON)}	V _{CE} =5.0V, I _C =100μA		0.70	V
hFF	V _{CF} =5.0V, I _C =10µA	150	600	
hFE	V _{CF} =5.0V, I _C =10µA, T _A =–55°C	30		
hFE	V _{CF} =5.0V, I _C =100μA	225		
hFE	V _{CE} =5.0V, I _C =1.0mA	300		
fT	V _{CF} =5.0V, I _C =500µA, f=20MHz	60		MHz
Ċ _{ob}	V _{CB} =5.0V, I _E =0, f=140kHz		6.0	pF
NF	$V_{CF}=5.0V, I_{C}=10\mu A, R_{S}=10k\Omega,$			
	f=1.0kHz, BW=200Hz		3.0	dB
h _{FF1} /h _{FF2}	V _{CE} =5.0V, I _C =100μA	0.8	1.0	
	V _{CE} =5.0V, I _C =10µA		10	mV
	V _{CF} =5.0V, I _C =100μA		5.0	mV
	V _{CF} =5.0V, I _C =1.0mA		10	mV
	V _{CF} =5.0V, I _C =100µA, T _A =–55°C to +25°C		1.6	mV
	V _{CE} =5.0V, I _C =100µA, T _A =+25°C to +125°C		2.0	mV

R1 (4-March 2011)



2N2918

DUAL SILICON NPN TRANSISTOR



	0	IMENSION	S	
	INCHES		MILLIM	ETERS
SYMBOL	MIN	MAX	MIN	MAX
	0 335	0.370	8 51	9.40

TO-78 CASE - MECHANICAL OUTLINE

R1

SYMBOL	MIN	MAX	MIN	MAX
A (DIA)	0.335	0.370	8.51	9.40
B (DIA)	0.305	0.335	7.75	8.51
С	0.150	0.185	3.81	4.70
D	-	0.040	-	1.02
E	0.500	-	12.70	-
F (DIA)	0.016	0.021	0.41	0.53
G	0.200		5.	08
Н	0.100		2.	54
J	0.028	0.034	0.71	0.86
K	0.029	0.045	0.74	1.14

TO-78 (REV: R1)

MARKING: FULL PART NUMBER

www.centralsemi.com

R1 (4-March 2011)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options

- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <u>www.centralsemi.com/terms</u>

www.centralsemi.com





http://www.centralsemi.com

Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

Summary: All transistors manufactured in the TO-78 package are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement	
CEN876	N/A	
CEN894	N/A	
CEN895	N/A	
CEN896	N/A	
CEN911	N/A	
CEN947	N/A	
CEN955 W/DATA	N/A	
MD2219A	N/A	
MD2369	N/A	
MD2369A	N/A	
MD2369B	N/A	
MD2905	N/A	
MD2905A	N/A	
MD5179	N/A	
MD7000	N/A	
MD7001	N/A	
MD7003	N/A	
MD7003A	N/A	
MD7003B	N/A	
MD8002	N/A	
MD8003	N/A	
MD918	N/A	
MD918A	N/A	
MD918B	N/A	
MD984	N/A	
2N2060	N/A	
2N2060A	N/A	
2N2060M	N/A	
2N2223	N/A	
2N2223A	N/A	
2N2453	N/A	
2N2453A	N/A	
2N2480	N/A	
2N2480A	N/A	
2N2639	N/A	
2N2640	N/A	
2N2641	N/A	
2N2642	N/A	
*** CONTINUED ***		

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



http://www.centralsemi.com

Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

*** CONTINUED FROM PRIOR PAGE ***

Central Part Number	Replacement
2N2643	N/A
2N2644	N/A
2N2652	N/A
2N2652A	N/A
2N2720	N/A
2N2721	N/A
2N2722	N/A
2N2903	N/A
2N2903A	N/A
2N2913	N/A
2N2914	N/A
2N2915	N/A
2N2915A	N/A
2N2916	N/A
2N2916A	N/A
2N2917	N/A
2N2918	N/A
2N2919	N/A
2N2919A	N/A
2N2920	N/A
2N2920A	N/A
2N3726	N/A
2N3727	N/A
2N3806	N/A
2N3807	N/A
2N3808	N/A
2N3809	N/A
2N3810	N/A
2N3810A	N/A
2N3811	N/A
2N3811A	N/A
2N4015	N/A
2N4016	N/A
2N4854	N/A
2N4937	N/A
2N4938	N/A
2N4939	N/A
2N5793	N/A
2N5794	N/A
2N5796	N/A
2N5912	N/A
2N6502	N/A

*** CONTINUED ***

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.



http://www.centralsemi.com

Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

*** CONTINUED FROM PRIOR PAGE ***

Central Part Number Replacement

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.