



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

## Normally – OFF Silicon Carbide Super Junction Transistor



<b>V<sub>DS</sub></b>	=	<b>650 V</b>
<b>V<sub>DS(ON)</sub></b>	=	<b>1.7 V</b>
<b>I<sub>D</sub></b>	=	<b>4 A</b>
<b>R<sub>DS(ON)</sub></b>	=	<b>415 mΩ</b>

### Features

- 250 °C maximum operating temperature
- Temperature independent switching performance
- Gate oxide free SiC switch
- Suitable for connecting an anti-parallel diode
- Positive temperature coefficient for easy paralleling
- Low gate charge
- Low intrinsic capacitance

### Package

- RoHS Compliant



SMD0.5 / TO – 276 (Hermetic Package)

### Advantages

- Low switching losses
- Higher efficiency
- High temperature operation
- High short circuit withstand capability

### Applications

- Down Hole Oil Drilling, Geothermal Instrumentation
- Hybrid Electric Vehicles (HEV)
- Solar Inverters
- Switched-Mode Power Supply (SMPS)
- Power Factor Correction (PFC)
- Induction Heating
- Uninterruptible Power Supply (UPS)
- Motor Drives

### Maximum Ratings at T<sub>j</sub> = 250 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values	Unit
Drain – Source Voltage	V <sub>DS</sub>	V <sub>GS</sub> = 0 V	650	V
Continuous Drain Current	I <sub>D</sub>	T <sub>C</sub> = 165 °C	4	A
Gate Peak Current	I <sub>GM</sub>		5	A
Reverse Gate – Source Voltage	V <sub>GS</sub>		200	V
Reverse Drain – Source Voltage	V <sub>DS</sub>		40	V
Power Dissipation	P <sub>tot</sub>	T <sub>C</sub> = 25 °C	7	W
Operating and Storage Temperature	T <sub>j</sub> , T <sub>stg</sub>		-55 to 250	°C

### Electrical Characteristics at T<sub>j</sub> = 250 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values		
			min.	typ.	max.

#### On Characteristics

Drain – Source On Voltage	V <sub>DS(ON)</sub>	I <sub>D</sub> = 4 A, I <sub>G</sub> = 100 mA, T <sub>j</sub> = 25 °C	1.7	V
		I <sub>D</sub> = 4 A, I <sub>G</sub> = 250 mA, T <sub>j</sub> = 175 °C	3.2	
		I <sub>D</sub> = 4 A, I <sub>G</sub> = 250 mA, T <sub>j</sub> = 250 °C	4.7	
Drain – Source On Resistance	R <sub>DS(ON)</sub>	I <sub>D</sub> = 4 A, I <sub>G</sub> = 100 mA, T <sub>j</sub> = 25 °C	415	mΩ
		I <sub>D</sub> = 4 A, I <sub>G</sub> = 250 mA, T <sub>j</sub> = 175 °C	820	
		I <sub>D</sub> = 4 A, I <sub>G</sub> = 250 mA, T <sub>j</sub> = 250 °C	1310	
Gate Forward Voltage	V <sub>GS(FWD)</sub>	I <sub>G</sub> = 500 mA, T <sub>j</sub> = 25 °C	3.3	V
		I <sub>G</sub> = 500 mA, T <sub>j</sub> = 250 °C	3.2	
DC Current Gain	β	V <sub>DS</sub> = 5 V, I <sub>D</sub> = 5 A, T <sub>j</sub> = 25 °C	120	nA
		V <sub>DS</sub> = 5 V, I <sub>D</sub> = 5 A, T <sub>j</sub> = 250 °C	85	

#### Off Characteristics



Drain Leakage Current	I <sub>DSS</sub>	V <sub>R</sub> = 650 V, V <sub>GS</sub> = 0 V, T <sub>j</sub> = 25 °C	7	nA
		V <sub>R</sub> = 650 V, V <sub>GS</sub> = 0 V, T <sub>j</sub> = 175 °C	25	
		V <sub>R</sub> = 650 V, V <sub>GS</sub> = 0 V, T <sub>j</sub> = 250 °C	105	

**Electrical Characteristics at  $T_J = 250^\circ\text{C}$ , unless otherwise specified**

Parameter	Symbol	Conditions	Values		
			min.	typ.	max.
<b>Dynamic Characteristics</b>					
Input Capacitance	$C_{iss}$	$V_{DS} = 35 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}, T_J = 25^\circ\text{C}$	324		pF
Output Capacitance	$C_{oss}$		45		pF
Reverse Transfer Capacitance	$C_{rss}$		45		pF
<b>Switching Characteristics</b>					
Turn On Delay Time	$t_{d(on)}$	$V_{DD} = 400 \text{ V}, I_D = 5 \text{ A}, R_{G(on)} = R_{G(off)} = 44 \Omega, V_{GS} = -8/15 \text{ V}, T_J = 175^\circ\text{C}$ Refer to Figure 10 for gate drive current waveforms	5		ns
Rise Time	$t_r$		15		ns
Turn Off Delay Time	$t_{d(off)}$		74		ns
Fall Time	$t_f$		14		ns
Turn-On Energy Per Pulse	$E_{on}$		24		$\mu\text{J}$
Turn-Off Energy Per Pulse	$E_{off}$		7		$\mu\text{J}$
Total Switching Energy	$E_{ts}$		31		$\mu\text{J}$
Turn On Delay Time	$t_{d(on)}$		9		ns
Rise Time	$t_r$	$V_{DD} = 400 \text{ V}, I_D = 5 \text{ A}, R_{G(on)} = R_{G(off)} = 44 \Omega, V_{GS} = -8/15 \text{ V}, T_J = 250^\circ\text{C}$ Refer to Figure 10 for gate drive current waveforms	24		ns
Turn Off Delay Time	$t_{d(off)}$		114		ns
Fall Time	$t_f$		17		ns
Turn-On Energy Per Pulse	$E_{on}$		54		$\mu\text{J}$
Turn-Off Energy Per Pulse	$E_{off}$		10		$\mu\text{J}$
Total Switching Energy	$E_{ts}$		64		$\mu\text{J}$

**Thermal Characteristics**

Thermal resistance, junction - case	$R_{thJC}$	1.6	$^\circ\text{C/W}$
-------------------------------------	------------	-----	--------------------


**Figure 1: Typical Output Characteristics at  $25^\circ\text{C}$** 

**Figure 2: Typical Output Characteristics at  $175^\circ\text{C}$**




Figure 3: Typical Output Characteristics at  $250^\circ\text{C}$




Figure 4: Typical Gate Source I-V Characteristics vs. Temperature




Figure 5: Normalized On-Resistance and Current Gain vs. Temperature




Figure 6: Typical Blocking Characteristics




Figure 7: Typical Capacitance vs Drain-Source Voltage




Figure 8: Typical Turn On Energy Losses and Switching Times vs. Temperature




Figure 9: Typical Turn Off Energy Losses and Switching Times vs. Temperature





Figure 10: Typical Gate-Source Switching Waveforms

### Package Dimensions:



#### NOTE

1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS

<b>Revision History</b>			
Date	Revision	Comments	Supersedes
2012/08/24	0	Initial release	

## Published by

GeneSiC Semiconductor, Inc.  
43670 Trade Center Place Suite 155  
Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.