



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CATALOG LISTING

2TP7-70

PAGE 1 OF 1

REPLACES

RELEASE NO. PR-19477

CHECK

REVISIONS

A C094415

TSM

24NOV99

CHECK

SAV

24NOV99

CHECK

PTC/CAD

2D

DRAWN

TSM

24NOV99

MICRO SWITCH  
a Honeywell Division  
FED. MFG. CODE 91929

SWITCH - TOGGLE  
ABOVE PANEL MOUNT

CATALOG LISTING  
2TP7-70

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

CIRCUIT DIAGRAM

LUG SIDE  
(MOMENTARY POSITION)

CENTER  
(MAINTAINED POSITION)

OPPOSITE LUG  
(MOMENTARY POSITION)

4X SR .08

1.07

.44

.77

.906

.18

1.812±.010

2.17

IDENTIFICATION LUG

BLACK PLASTIC LEVER

16°±3°  
TOTAL TRAVEL

.53

1.10

1.35

.130 MIN

.24

2X 6-32 UNC-2B THREAD  
WITH LOCKING FEATURE

BUSHING AND COVER  
SEALED TO PREVENT  
ENTRANCE OF LIQUIDS  
OR DUST

.130 MIN

.250

1.32

.28

.75

.38

.26

.89

.38

6X 6-32 UNC-2 X (.260)  
BINDING HEAD TERMINAL  
SCREW AND LOCKWASHER  
(SEMS) 3

ELECTRICAL DATA

L192

10A 125, 250, 277 VAC

1/4HP 125 VAC,

1/2HP 250, 277 VAC

3A 125 VAC "L"

CE

UL

NOTES

1 - SWITCH WILL WITHSTAND TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD

2 - MICRO SWITCH CATALOG LISTING MARKED ON SIDE OF SWITCH

3 - SCREWS FURNISHED UNASSEMBLED

ELECTRICAL DATA

MILITARY RATING (AMPS)

RESISTIVE LOAD		AC VOLTS		LAMP LOAD		INDUCTIVE LOAD		
DC VOLTS								
28	125	250	125	250	28 VDC	125 VAC	28 VDC	125 VAC
18	.75	.5	11	6	5	2	10	8

THIRD ANGLE PROJECTION

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ONE PLACE (.0) ±.030

TWO PLACE (.00) ±.015

THREE PLACE (.000) ±.005

ANGLES ±

WEIGHT .14 LB EST

ANSI Y14.5M-1982 APPLIES