



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com



Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	30NOV2013	YC	BvH
	A1	ECR-14-015049	13OCT2014	GSK	BvH
	A2	ECR-16-003945	16MAR2016	GSK	BvH

NOTES:
 Tolerances cable lengths:
 0m to 0.5m +30mm
 0.5m to 1.0m +50mm
 1.0m to 3.0m +100mm
 < 3.0m +1.5%



TECHNICAL DATA	
Operating voltage	24 V DC ±25 %
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 x 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

PUR/PVC CABLE	
No./diameter of wires	4 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk)
C-track properties	2 million
Jacket	PUR/PVC
Outer diameter	approx. 5.2 mm
Bend radius (moving)	15 x outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

CABLE	
No./diameter of wires	4 x 0.34 mm ²
Wire isolation	PP (br, wh, bl, bk)
C-track properties	10 million
Jacket	PUR (UL/CSA), welding spark res.
Outer diameter	approx. 4.7 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-40...+90 °C
Temperature range (mobile)	-25...+90 °C

LENGTH "L"	MATERIAL	JACKET COLOR	TE PN	DESCRIPTION	ITEM
4 pos	SPARK RESISTANT	Black	3-2273126-5	4x22AWG SPARK RES 2.0m	20
			3-2273126-4	4x22AWG SPARK RES 1.5m	19
			3-2273126-3	4x22AWG SPARK RES 1.0m	18
			3-2273126-2	4x22AWG SPARK RES 0.6m	17
			3-2273126-1	4x22AWG SPARK RES 0.3m	16
4 pos	PUR/PVC	Black	2-2273126-5	4x22AWG PUR/PVC 2.0m	15
			2-2273126-4	4x22AWG PUR/PVC 1.5m	14
			2-2273126-3	4x22AWG PUR/PVC 1.0m	13
			2-2273126-2	4x22AWG PUR/PVC 0.6m	12
			2-2273126-1	4x22AWG PUR/PVC 0.3m	11

TECHNICAL DATA	
Operating voltage	24 V DC ±25 %
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 x 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

PUR CABLE	
No./diameter of wires	4 x 0.34 mm ²
Wire isolation	PP (br, wh, bl, bk)
C-track properties	5 million
Jacket	PUR (UL/CSA)
Outer diameter	approx. 4.7 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-25...+80 °C

PVC CABLE	
No./diameter of wires	4 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk)
C-track properties	
Jacket	PVC (UL/CSA)
Outer diameter	approx. 5.0 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

LENGTH "L"	MATERIAL	JACKET COLOR	TE PN	DESCRIPTION	ITEM
4 pos	PVC	Black	1-2273126-5	4x22AWG PVC 2.0m	10
			1-2273126-4	4x22AWG PVC 1.5m	9
			1-2273126-3	4x22AWG PVC 1.0m	8
			1-2273126-2	4x22AWG PVC 0.6m	7
			1-2273126-1	4x22AWG PVC 0.3m	6
4 pos	PUR	Black	2273126-5	4x22AWG PUR 2.0m	5
			2273126-4	4x22AWG PUR 1.5m	4
			2273126-3	4x22AWG PUR 1.0m	3
			2273126-2	4x22AWG PUR 0.6m	2
			2273126-1	4x22AWG PUR 0.3m	1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN YATHISH.C 30NOV2013	TE TE Connectivity	
DIMENSIONS: mm		CHK B.VELDHOVEN 30NOV2013		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD A.VAN ZANDVOORT 30NOV2013	NAME M12 ANGLD SCKT TO M12 STRGHT PLG 3 LED	
0 PLC ± -		PRODUCT SPEC 108-19483	RESTRICTED TO	
1 PLC ± -		APPLICATION SPEC 114-32127	SIZE A2	CAGE CODE 00779
2 PLC ± -		WEIGHT	DRAWING NO C=2273126	SCALE NTS
3 PLC ± -		CUSTOMER DRAWING	SHEET 1 OF 1	REV A2
4 PLC ± -				
ANGLES ± -				
FINISH				