



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Ratings**

Voltage: 150 V  
 Temperature: 80° C  
 Flammability: VW-1

**Conductor**

Conductor count: 4  
 Gauge: 0.034 mm<sup>2</sup>  
 Material: tinned copper strands  
 Strand size: Ø 0.08 mm x 7

**Insulator**

Material: LD-PE  
 Color: white, black, red, yellow  
 Diameter: 0.55 ±0.5 mm  
 Nominal thickness: 0.15 mm

**Filler**

Material: nylon 500D

**Shield**



Type: spiral  
 Material: tinned copper strands  
 Stranding: Ø 0.127 x 36  
 Coverage: 85% minimum

**Outer jacket**

Material: soft PVC  
 Color: black  
 Diameter: 2.0 ±0.15 mm  
 Nominal thickness: 0.25 mm

**Wire marking:** none

**Use:** Internal wiring or external interconnection of electronic equipment.



Revision:	Date:	Description:	Prepared: GL 2016.07.08 08:24:41 -07'00'	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118          fax 1.541.323.4202 web tensility.com</p>
A	1/29/2013	Initial releas	Verified: AG 2016.07.08 12:27:48 -07'00'	RoHS and REACH compliant	
A1	6/7/2013	Updated spec format	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent	
A2	7/6/2016	Corrected conductor stranding		Description:	Description: Wire, 4C, 32 AWG, 150V, 80C, 2.0 mm, spiral shield, VW-1, PVC, 66A Size: A Part number: 30-00217
					Scale: 10:1 Sheet 1 of 1