

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Ratings

Temperature: 0 ~ 70 °C

Voltage: 150 V

Conductor

Gauge: 32 AWG, 0.039 mm² Material: tinned copper strands Stranding: \emptyset 0.05 x 19

Resistance at 20 °C: $590 \Omega/km$

Insulator

Material: HDPE

Color: black, white, red

Outer diameter: \emptyset 0.55 ±0.05 mm Nominal thickness: 0.15 mm Resistance at 20 °C: 1000 M Ω /km

Shield

Type: spiral

Material: tinned copper strands

Strand size: \emptyset 0.08 mm Coverage: 90 % minimum

Outer jacket Material: TPU, 70 °C Color: white, cool gray 1C Nominal thickness: 0.50 mm Diameter: \emptyset 2.5 ±0.15 mm

Filler


Material: kevlar


Tests

Tensile strength: 25.5 kgf

Dielectric test: 1500 V dc for 1 minute without breakdown Bend test at 200 g, $\pm 90^{\circ}$, 30 cycles /min: 10,000 cycle

minimum





REVISION	DATE	DESCRIPTION	PREPARED:		NOTES		_				
Α	4/22/2015	Initial release	AG 2016.01.		RoHS and REACH compliant		TENSILITY				
A 1	1/12/2016	H- d-t- dtt- d t-l	VERIFIED:		Jacket meets ISO 10993 Biologi	cal Compatibility	20802 Sockeye Place #130				
A1	1/13/2016	Updated notes, corrected tolerance	Digitally signed by DN: cn=LA, o=Ten ou=Engineering, email—QM002/EP Date: 2016.01.13 1	nsility com cul IS	Phthalate and halogen free			Bend, OR 97701 USA tel 541.323.3228 fax 541.323.4202			
			DIMENSIONS ARE IN MILLIMETERS		Function test: no open, no short, no intermittent		800 877.670.7118 www.tensility.com				
					DESCRIPTION: Wire, 3C, 32 AWG, 150V, 80C, 2.5 mm, spiral shield, TPU, white		SIZE	PART NUMBER			
							Α	30-00454			
							SCALI	E: 1:1		SHEET 1 OF 1	

5 3