

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Ratings

Voltage: 300 V

Operating temperature: -20° to 80 °C

Conductor

Gauge: 24 AWG, 0.22 mm<sup>2</sup> Material: tinned copper strands

Strand size: Ø 0.16 mm Strand count: 11

Max resistance at 20 °C:  $94.2 \Omega/km$ 

Insulator

Material: PVC Color: white

Outer diameter: 1.4 ±0.10 mm Min resistance at 20 °C: 10 M $\Omega$ /km

Shield

Type: spiral

Material: tinned copper strands

Strand size: Ø 0.12 mm Strand count: 35 ±2

**Outer iacket** 

Material: TPU, 80 °C

Type: extruded, non-integral

Color: grav

Diameter: 3.4 ±0.15 mm

**Wire marking**: E339579 **%** AWM STYLE 10846 80°C 300V Vw-1 - - - C **%** AWM I/II A 80°C 300V FT1 TENSILITY

Tests

Voltage test: 300 V Spark test: 3.0 kV


Tensile strength: 1.05 kgf/mm<sup>2</sup> After aging at 113 ±2 °C for 7 days: Minimum tensile strength 70 % original Minimum elongation 65 % original

Heat shock:  $121 \pm 1$  °C /1 hour, no observed degradation

Deformation:  $121 \pm 1$  °C /1 hour,  $\leq 50$  % Cold bend:  $-10 \pm 1$  °C /1 hour, no observed cracking

Flammability: FT1, VW-1

Dielectric test: 1500 V ac for 1 minute without breakdown



REVISION		DESCRIPTION Lesis and Lesi	PREPARED: 2016.03.11 10:38:08	NOTES RoHS and REACH compliant		T	TENSILITY		
Α	9/3/2015	Initial release	VERIFIED:	Function test: no open, no short circuit, no intermittent  Drawing in third angle projected		20802 Sockeye Place #130 Bend, OR 97701 USA tel 541.323.3228 fax 541.323.4202 800 877.670.7118 www.tensility.com			
A1	9/14/2015	Upgraded fire rating to VW-1/ FT1	Digitally signed by PS  Digita						
A2	3/10/2016	Updated operating temperature range	DIMENSIONS ARE IN						
			TOLERANCES:  X: ± 0.5 mm  X.X: ± 0.3 mm  X.XX: ± 0.05 mm	DESCRIPTION: Wire, 1C TS, 24 AWG, UL10846, 300V, 80C, 3.4 mm, shielded, VW-1, TPU, gray		SIZE PART NUMBER A 30-00569			
						SCALE	: 12:1		SHEET 1 OF 1
		5	4	3	2	•		•	1