



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Ratings

Voltage: 300 V
Temperature: 80 °C
Flammability: VW-1, FT1

Conductor

Conductor count: 2
Gauge: 24 AWG, 0.22 mm²
Material: tinned copper strands
Stranding: $\phi 0.16 \times 11$
Resistance at 20 °C: 95 ohm/km maximum

Insulator

Material: SRPVC, 80 °C
Color: black, red
Outer diameter: $\phi 1.2 \pm 0.10$ mm
Thickness: 0.23 mm minimum average
Style: UL 1061

Outer jacket

Material: PVC, 80 °C
Color: white
Diameter: $\phi 4 \pm 0.20$ mm
Thickness: 0.76 mm minimum average


Wire marking: E339579 UL AWM STYLE 2464 24AWG 80°C
300V VW-1 --- cUL AWM I A 80°C 300V FT1 TENSILITY

Tests

Tensile strength: 1.05 kgf/mm²
After aging at 113 ± 2 °C for 7 days:
Minimum tensile strength 70 % original
Minimum elongation 65 % original
Flexibility: no observed cracking
Heat shock: 121 ± 1 °C / 1 hour, no observed degradation
Deformation: 121 ± 1 °C / 1hour, ≤ 50 %
Cold bend: -10 ± 2 °C / 1 hour, no observed cracking
Dielectric: 2000 Vac for 1 minute without breakdown

Use:

Internal wiring or external interconnection of electronic equipment



REVISION	DATE	DESCRIPTION
A	1/22/2016	Initial release

PREPARED:
AG 2016.01.22
08:41:43
-08'00'

VERIFIED:
LA Digitally signed by LA, DN: cn=LA, o=Tensility, email=LA@tensility.com, c=US, Date: 2016.01.22 16:55:04 -0800

DIMENSIONS ARE IN MILLIMETERS

TOLERANCES:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

NOTES
RoHS and REACH compliant

Function test: no open, no short circuit, no intermittent

Meets UL appliance wiring standard 758

DESCRIPTION:
Wire, 2C TS, 24 AWG, UL2464, 300V, 80C, 4.0 mm, VW-1, PVC, white

TENSILITY

20802 Sockeye Place #130
Bend, OR 97701 USA
tel 541.323.3228 fax 541.323.4202
800 877.670.7118 www.tensility.com

SIZE A	PART NUMBER 30-00693
SCALE: 12:1	
SHEET 1 OF 1	