



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Low-Heat Shrinkable Tubing 2:1

TCN20 - self extinguishing

TCN20 is suitable for a wide range of applications such as electrical insulation, mechanical protection and cable bundling.

Features and Benefits

- Thin walled general purpose polyolefin tubing
- Highly flame-retardant, UL224 VW-1 , CSA
- Fast shrinking
- Low shrink temperature



Heat Shrink Tubing TCN20.



Detailed Information about Heatguns please refer to page 529.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	2:1
Operating Temperature	-55 °C to +125 °C
Minimum Shrink Temperature	+100 °C
Longitudinal change after shrinkage	+/-5 %
Dielectric Strength	20kV/mm according to ASTM D2671
Flammability	Self extinguishing
Specifications	CSA, UL224 125 °C 600V VW-1



RoHS

TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Article-No.
TCN20-1.2/0.6	1.2	3/64 "	0.6	0.30	300 m	Black (BK)	300-73010
TCN20-1.6/0.8	1.6	1/16 "	0.8	0.35	300 m	Black (BK)	300-73020
TCN20-2.4/1.2	2.4	3/32 "	1.2	0.45	300 m	Black (BK)	300-73030
TCN20-3.2/1.6	3.2	1/8 "	1.6	0.45	300 m	Black (BK)	300-73040
TCN20-4.8/2.4	4.8	3/16 "	2.4	0.50	300 m	Black (BK)	300-73050
TCN20-6.4/3.2	6.4	1/4 "	3.2	0.55	300 m	Black (BK)	300-73060
TCN20-9.5/4.8	9.5	3/8 "	4.8	0.55	100 m	Black (BK)	300-73070
TCN20-12.7/6.4	12.7	1/2 "	6.4	0.65	100 m	Black (BK)	300-73080
TCN20-19.1/9.5	19.1	3/4 "	9.5	0.80	60 m	Black (BK)	300-73090
TCN20-25.4/12.7	25.4	1 "	12.7	0.90	60 m	Black (BK)	300-73100
TCN20-38.1/19.1	38.1	1-1/2 "	19.1	1.02	30 m	Black (BK)	300-73110
TCN20-50.8/25.4	50.8	2 "	25.4	1.15	30 m	Black (BK)	300-73120

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.