



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Specification Sheet

Part Number: 300-73607



Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, .50" Supp/.25" Recov Dia, PO-X, Black, 500ft/reel

**Article Number**

300-73607

**Type**

TCN20-12.7/6.4

**Color**

Black (BK)

**Features & Benefits**

- Tubing is 2:1, thin wall and self extinguishing providing good resistance to common fluids and solvents.
- Low shrink temperature gives excellent physical and electrical performance.
- Available in multiple diameters and lengths offering several options to fit specific needs.

**Quantity Per**

box

**Product Description**

TCN20 Heat Shrink is a general purpose, thin wall tubing used to protect electrical and mechanical wiring. Polyolefin material is self extinguishing and resistant against common fluids and solvents. The low shrink temperature and mechanical strength make this tubing widely used in the electric and electronics industry. Available in a wide range of diameters up to 2.0 (50.8mm) and multiple lengths. TCN20 Heat Shrink is UL224 125 °C 600V VW-1 and RoHS.

**Short Description**

Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, .50" Supp/.25" Recov Dia, PO-X, Black, 500ft/reel

**Global Part Name**

TCN20-12.7/6.4-PO-X-BK

**Length L (Imperial)**

500.0

**Length L (Metric)**

152.4

**Variant**

Thin-Wall

**Nominal Diameter (Imperial)**

1/2

**Nominal Diameter (Metric)**

12.7

**Wall Thickness WT (Metric)**

0.65

**Material**

Polyolefin, cross-linked (PO-X)

**Material Shortcut**

PO-X

**Flammability**

Self-Extinguishing

**Halogen free**

No

**Operating Temperature (Metric)**

-67°F to +257°F (-55°C to +125°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Certification/Specification WEB**

UL 224 125 °C 600V VW-1 CSA | C22.2 no. 198.1-06

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

500

**Package Quantity (Metric)**

152.4

**Customs Number**

3926909987