

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Electronic device circuit breaker - EC 1 12DC/2A S-R - 3000761

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Electronic circuit breaker, reset input and status output, nominal current: 2 A



Key Commercial Data

Packing unit	10 STK
GTIN	4 046356 708555
GTIN	4046356708555

Technical data

General

Mounting type	DIN rail: 35 mm
Color	black

Dimensions

Height	80 mm
Width	12.5 mm

Ambient conditions

Ambient temperature (operation)	-20 °C 60 °C (ordinary locations)

Connection data

Conductor cross section solid min.	0.5 mm²	
Conductor cross section solid max.	10 mm ²	
Conductor cross section flexible min.	0.5 mm²	
Conductor cross section flexible max.	10 mm ²	
2 conductors with same cross section, solid min.	0.5 mm²	
2 conductors with same cross section, solid max.	4 mm²	
2 conductors with same cross section, stranded min.	0.5 mm²	
2 conductors with same cross section, stranded max.	4 mm²	



Electronic device circuit breaker - EC 1 12DC/2A S-R - 3000761

Technical data

Connection data

Connection method	Screw connection
Stripping length	10 mm
Screw thread	M4
Tightening torque, min	1.5 Nm
Tightening torque max	1.8 Nm

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1	
China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Approvals

Approvals

Approvals

UL Recognized / UL Recognized / cUL Recognized / EAC / UL Listed / CUL Listed / GL / cULus Recognized / cULus Listed

Ex Approvals

UL Recognized

Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 140324

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 317172

cUL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 140324

EAC RU C-DE.A*30.B01546



Electronic device circuit breaker - EC 1 12DC/2A S-R - 3000761

Approvals

UL Listed	UL	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
cUL Listed	C UL	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
GL	(GL)	http://exchange.dnv.com/tari/	14505-15 HH
cULus Recognized	C UL US	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	
cULus Listed			

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com