

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# Plug-in bridge - FBSR 10-6 - 3033716

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red



## **Key Commercial Data**

| Packing unit | 10 STK          |
|--------------|-----------------|
| GTIN         | 4 046356 590938 |
| GTIN         | 4046356590938   |

### Technical data

#### Technical data

| Color                                  | red   |
|--|---|
| Material                               | Copper  |
| Number of positions                    | 10  |
| Pitch                                  | 6.2 mm  |
| Flammability rating according to UL 94 | V0  |
| Maximum load current                   | 24 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |

#### Standards and Regulations

| Flammability rating according to UL 94 | V0 |
|--|----|

#### **Environmental Product Compliance**

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com