



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Antenna/ RFID Rods (3061990881)



Part Number: 3061990881

61 ROD

Explanation of Part Numbers:

- Digits 1 & 2 = Product Class
- Digits 3 & 4 = Material Grade
- ☐ – The last digit 1 = Uncoated Rod and 4 = Parylene Coated Rod. Parylene C is RoHS compliant.

These rods are designed for use in antenna and RFID transponder applications. Rods are available in three materials to cover a frequency range from 50 kHz to 25 MHz. Suggested frequency ranges: 78 material < 200 kHz, 61 material 0.2 – 5.0 MHz and 67 material > 5.0 MHz.

The “Antenna/ RFID Kit” (part number 0199000024) contains a selection of these rods.

☐ **For any rod requirement not listed here, feel free to contact our customer service group for availability and pricing.**

Weight: 1.8 (g)

| Dim | mm | mm tol | nominal inch | inch misc. |
|-----|----|--------|--------------|------------|
| A | 4 | ±0.04 | 0.157 | — |
| C | 30 | ±0.75 | 1.181 | — |

| Electrical Properties | |
|-----------------------|-------|
| μ_{ROD} | 25 |
| $A_e(\text{cm}^2)$ | 0.126 |