



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Fuse - FUSE 10,3X85 4A PV - 3062767

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse, 10.3 mm x 85 mm, up to 1500 V DC, gPV characteristic



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
Custom tariff number	85361010
Country of origin	Slovenia

Technical data

Environmental Product Compliance

China RoHS	No hazardous substances above threshold values
------------	--

General

Color	white
Flammability rating according to UL 94	V0

Dimensions

Length	85 mm
Diameter	10.3 mm

General

Fuse	Midget/10.3 x 85
Connection in acc. with standard	IEC 60269-6
Nominal current I_N	4 A
Nominal voltage U_N	1500 V AC/DC

Standards and Regulations

Fuse - FUSE 10,3X85 4A PV - 3062767

Technical data

Standards and Regulations

Connection in acc. with standard	IEC 60269-6
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27142001
eCl@ss 4.1	27142001
eCl@ss 5.0	27142001
eCl@ss 5.1	27142002
eCl@ss 6.0	27142002
eCl@ss 7.0	27142002
eCl@ss 8.0	27142002
eCl@ss 9.0	27142002

ETIM

ETIM 3.0	EC000035
ETIM 4.0	EC002704
ETIM 5.0	EC002704

UNSPSC

UNSPSC 6.01	30211915
UNSPSC 7.0901	39121514
UNSPSC 11	39121514
UNSPSC 12.01	39121514
UNSPSC 13.2	39121514