



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Aluminum Capacitors

## +105 °C, Miniature, Axial Lead, General Purpose


**FEATURES**

- Long life
- High performance
- High CV per case size
- Case sizes to 0.709" [18.0 mm] diameters
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

| QUICK REFERENCE DATA                    |  |
|---|--|
| DESCRIPTION                             | VALUE  |
| Nominal case size<br>Ø D x L in mm      | 0.248" x 0.512" [6.3 x 13.0]<br>to 0.709" x 1.574" [18.0 x 40.0]   |
| Operating temperature                   | -40 °C to +105 °C  |
| Rated capacitance range, C <sub>R</sub> | 1 µF to 4700 µF  |
| Tolerance on C <sub>R</sub>             | ± 20 %   |
| Rated voltage range, U <sub>R</sub>     | 3 WV <sub>DC</sub> to 250 WV <sub>DC</sub>   |
| Termination                             | Axial leads  |
| Life validation test at 105 °C          | 2000 h:<br>ΔCAP ≤ 20 % from initial measurement.<br>ΔESR ≤ 1.5 x initial specified limit.<br>ΔDCL ≤ initial specified limit.                                       |
| Shelf life at 85 °C                     | 500 h:<br>ΔCAP ≤ 20 % from initial measurement.<br>ΔESR ≤ 1.5 x initial specified limit.<br>ΔDCL ≤ 2.0 x initial specified limit.                                  |
| DC leakage current                      | 3 WV <sub>DC</sub> to 16 WV <sub>DC</sub> :<br>I = 0.1 √CV + 2<br>25 WV <sub>DC</sub> to 250 WV <sub>DC</sub> :<br>I = 0.2 √CV + 2<br>I in µA, C in µF, V in Volts |

| RIPPLE CURRENT MULTIPLIERS |          |             |            |            |
|----------------------------|----------|-------------|------------|------------|
| TEMPERATURE                |          |             |            |            |
| AMBIENT TEMPERATURE        |          | MULTIPLIERS |            |            |
| +105 °C                    |          | 0.5         |            |            |
| +85 °C                     |          | 1.0         |            |            |
| ≤ 65 °C                    |          | 2.0         |            |            |
| FREQUENCY (Hz)             |          |             |            |            |
| WV <sub>DC</sub>           | 50 TO 60 | 100 TO 120  | 300 TO 400 | 1K TO 100K |
| 3 to 50                    | 0.9      | 1.0         | 1.1        | 1.4        |
| 51 to 250                  | 0.8      | 1.0         | 1.3        | 1.6        |

| DIMENSIONS in inches [millimeters] |                |                |                |                |                                   |                |
|------------------------------------|----------------|----------------|----------------|----------------|-----------------------------------|----------------|
| CASE CODE                          | NOMINAL        |                | STYLE 2        |                | STYLE 5<br>RESIN END SEAL APPLIED |                |
|                                    | D              | L              | D (max.)       | L (max.)       | D (max.)                          | L (max.)       |
| BA                                 | 0.248 [6.300]  | 0.512 [13.000] | 0.276 [7.000]  | 0.567 [14.400] | 0.276 [7.000]                     | 0.626 [15.900] |
| BB                                 | 0.248 [6.300]  | 0.689 [17.500] | 0.276 [7.000]  | 0.756 [19.200] | 0.276 [7.000]                     | 0.815 [20.700] |
| CB                                 | 0.315 [8.000]  | 0.689 [17.500] | 0.339 [8.600]  | 0.756 [19.200] | 0.339 [8.600]                     | 0.815 [20.700] |
| CC                                 | 0.315 [8.000]  | 0.807 [20.500] | 0.339 [8.600]  | 0.878 [22.300] | 0.339 [8.600]                     | 0.937 [23.800] |
| DC                                 | 0.374 [9.500]  | 0.807 [20.500] | 0.402 [10.200] | 0.878 [22.300] | 0.402 [10.200]                    | 0.937 [23.800] |
| DD                                 | 0.374 [9.500]  | 0.945 [24.000] | 0.402 [10.200] | 1.01 [25.500]  | 0.402 [10.200]                    | 1.063 [27.000] |
| DF                                 | 0.374 [9.500]  | 1.260 [32.000] | 0.402 [10.200] | 1.319 [33.500] | 0.402 [10.200]                    | 1.378 [35.000] |
| DH                                 | 0.374 [9.500]  | 1.496 [38.000] | 0.402 [10.200] | 1.567 [39.800] | 0.402 [10.200]                    | 1.626 [41.300] |
| EF                                 | 0.433 [11.000] | 1.260 [32.000] | 0.465 [11.800] | 1.319 [33.500] | 0.465 [11.800]                    | 1.378 [35.000] |
| EH                                 | 0.433 [11.000] | 1.496 [38.000] | 0.465 [11.800] | 1.567 [39.800] | 0.465 [11.800]                    | 1.626 [41.300] |
| FH                                 | 0.492 [12.500] | 1.496 [38.000] | 0.516 [13.100] | 1.567 [39.800] | 0.516 [13.100]                    | 1.626 [41.300] |
| FK                                 | 0.492 [12.500] | 1.752 [44.500] | 0.516 [13.100] | 1.831 [46.500] | 0.516 [13.100]                    | 1.890 [48.000] |
| GH                                 | 0.630 [16.000] | 1.496 [38.000] | 0.654 [16.600] | 1.567 [39.800] | 0.654 [16.600]                    | 1.626 [41.300] |
| GK                                 | 0.630 [16.000] | 1.752 [44.500] | 0.654 [16.600] | 1.831 [46.500] | 0.654 [16.600]                    | 1.890 [48.000] |
| LS                                 | 0.709 [18.000] | 1.575 [40.000] | 0.736 [18.700] | 1.673 [42.500] | 0.736 [18.700]                    | 1.693 [43.000] |

**Note**

- Lead diameter AWG 20 (0.032" [0.81 mm])

**ORDERING EXAMPLE**

Electrolytic capacitor 30D series: 30D 128 M 025 EH 2 A

| DESCRIPTION |                                       |
|-------------|---------------------------------------|
| CODE        | EXPLANATION                           |
| 30D         | Product type                          |
| 128         | Capacitance value (1200 $\mu$ F)      |
| M           | Tolerance (M = $\pm$ 20 %)            |
| 025         | Voltage rating at 105 °C (024 = 25 V) |
| EH          | Can size (see Dimensions table)       |
| 2           | Sleeve and sealing (2 = mylar sleeve) |
| A           | Packaging (A = bulk)                  |

**Note**

- For lead (Pb)-free / RoHS-compliant products add suffix "E3" to part number.  
Example: 30D128M025EH2AE3

| ELECTRICAL DATA AND ORDERING INFORMATION           |                |                                    |   |   |
|--|----------------|------------------------------------|---|---|
| CAPACITANCE<br>( $\mu$ F)                          | PART NUMBER    | NOMINAL CASE SIZE<br>D x L<br>[mm] | MAX. ESR<br>AT +25 °C<br>120 Hz<br>( $\Omega$ ) | MAX. RIPPLE<br>AT +85 °C<br>120 Hz<br>(A) |
| <b>6.3 WV<sub>DC</sub> AT +105 °C, SURGE = 8 V</b> |                |                                    |   |   |
| 150.0  | 30D157M6R3BB2A | 0.248 x 0.689 [6.3 x 17.5]         | 2.875   | 0.163                                     |
| 330.0  | 30D337M6R3CC2A | 0.315 x 0.807 [8.0 x 20.5]         | 1.277   | 0.299                                     |
| 1200.0   | 30D128M6R3DF2A | 0.374 x 1.260 [9.5 x 32.0]         | 0.345   | 0.767                                     |
| 2200.0   | 30D228M6R3EF2A | 0.433 x 1.260 [11.0 x 32.0]        | 0.206   | 1.080                                     |
| 4700.0   | 30D478M6R3GH2A | 0.630 x 1.496 [16.0 x 38.0]        | 0.118   | 1.910                                     |
| <b>10 WV<sub>DC</sub> AT +105 °C, SURGE = 12 V</b> |                |                                    |   |   |
| 47.0   | 30D476M010BA2A | 0.248 x 0.512 [6.3 x 13.0]         | 7.487   | 0.089                                     |
| 100.0  | 30D107M010BB2A | 0.248 x 0.689 [6.3 x 17.5]         | 3.561   | 0.147                                     |
| 330.0  | 30D337M010CC2A | 0.315 x 0.807 [8.0 x 20.5]         | 1.081   | 0.325                                     |
| 470.0  | 30D477M010DC2A | 0.374 x 0.807 [9.5 x 20.5]         | 0.748   | 0.434                                     |
| 1000.0   | 30D108M010DF2A | 0.374 x 1.260 [9.5 x 32.0]         | 0.356   | 0.755                                     |
| 2200.0   | 30D228M010EH2A | 0.433 x 1.496 [11.0 x 38.0]        | 0.184   | 1.240                                     |
| <b>16 WV<sub>DC</sub> AT +105 °C, SURGE = 20 V</b> |                |                                    |   |   |
| 33.0   | 30D336M016BA2A | 0.248 x 0.512 [6.3 x 13.0]         | 9.814   | 0.078                                     |
| 150.0  | 30D157M016CB2A | 0.315 x 0.689 [8.0 x 17.5]         | 2.208   | 0.212                                     |
| 330.0  | 30D337M016DC2A | 0.374 x 0.807 [9.5 x 20.5]         | 1.981   | 0.379                                     |
| 470.0  | 30D477M016DD2A | 0.374 x 0.945 [9.5 x 24.0]         | 0.679   | 0.483                                     |
| 1200.0   | 30D128M016DH2A | 0.374 x 1.496 [9.5 x 38.0]         | 0.265   | 0.947                                     |
| 4700.0   | 30D478M016GK2A | 0.630 x 1.752 [16.0 x 44.5]        | 0.093   | 2.290                                     |
| <b>20 WV<sub>DC</sub> AT +105 °C, SURGE = 25 V</b> |                |                                    |   |   |
| 150.0  | 30D157M020CC2A | 0.315 x 0.807 [8.0 x 20.5]         | 2.110   | 0.233                                     |
| 220.0  | 30D227M020DC2A | 0.374 x 0.807 [9.5 x 20.5]         | 1.410   | 0.318                                     |
| 1000.0   | 30D108M020EF2A | 0.433 x 1.260 [11.0 x 32.0]        | 0.323   | 0.863                                     |
| 1500.0   | 30D158M020EH2A | 0.433 x 1.496 [11.0 x 38.0]        | 0.221   | 1.140                                     |
| 3300.0   | 30D338M020GK2A | 0.630 x 1.752 [16.0 x 44.5]        | 0.118   | 2.040                                     |





| <b>ELECTRICAL DATA AND ORDERING INFORMATION</b>    |                    |   |  |   |
|--|--------------------|---|--|---|
| <b>CAPACITANCE<br/>(<math>\mu</math>F)</b>         | <b>PART NUMBER</b> | <b>NOMINAL CASE SIZE<br/>D x L<br/>[mm]</b> | <b>MAX. ESR<br/>AT +25 °C<br/>120 Hz<br/>(<math>\Omega</math>)</b> | <b>MAX. RIPPLE<br/>AT +85 °C<br/>120 Hz<br/>(A)</b> |
| <b>25 WV<sub>DC</sub> AT +105 °C, SURGE = 35 V</b> |                    |   |  |   |
| 22.0   | 30D226M025BA2A     | 0.248 x 0.512 [6.3 x 13.0]                  | 13.270   | 0.067   |
| 47.0   | 30D476M025BB2A     | 0.248 x 0.689 [6.3 x 17.5]                  | 6.128  | 0.112   |
| 100.0  | 30D107M025CC2A     | 0.315 x 0.807 [8.0 x 20.5]                  | 2.914  | 0.197   |
| 220.0  | 30D227M025DC2A     | 0.374 x 0.807 [9.5 x 20.5]                  | 1.327  | 0.326   |
| 330.0  | 30D337M025DD2A     | 0.374 x 0.945 [9.5 x 24.0]                  | 0.885  | 0.423   |
| 470.0  | 30D477M025DF2A     | 0.374 x 1.260 [9.5 x 32.0]                  | 0.612  | 0.575   |
| 1200.0   | 30D128M025EH2A     | 0.433 x 1.496 [11.0 x 38.0]                 | 0.239  | 1.090   |
| 3300.0   | 30D338M025LS2A     | 0.709 x 1.575 [18.0 x 40.0]                 | 0.108  | 2.190   |
| <b>35 WV<sub>DC</sub> AT +105 °C, SURGE = 45 V</b> |                    |   |  |   |
| 33.0   | 30D336M035BB2A     | 0.248 x 0.689 [6.3 x 17.5]                  | 8.330  | 0.096   |
| 100.0  | 30D107M035DC2A     | 0.374 x 0.807 [9.5 x 20.5]                  | 2.740  | 0.212   |
| 220.0  | 30D227M035DD2A     | 0.374 x 0.945 [9.5 x 24.0]                  | 1.250  | 0.356   |
| 330.0  | 30D337M035DF2A     | 0.374 x 1.260 [9.5 x 32.0]                  | 0.830  | 0.495   |
| 1000.0   | 30D108M035EH2A     | 0.433 x 1.496 [11.0 x 38.0]                 | 0.274  | 1.020   |
| 2200.0   | 30D228M035GK2A     | 0.630 x 1.752 [16.0 x 44.5]                 | 0.125  | 1.980   |
| <b>40 WV<sub>DC</sub> AT +105 °C, SURGE = 50 V</b> |                    |   |  |   |
| 15.0   | 30D156M040BA2A     | 0.248 x 0.512 [6.3 x 13.0]                  | 17.600   | 0.058   |
| 22.0   | 30D226M040BB2A     | 0.248 x 0.689 [6.3 x 17.5]                  | 11.700   | 0.081   |
| 47.0   | 30D476M040CB2A     | 0.315 x 0.689 [8.0 x 17.5]                  | 5.435  | 0.134   |
| 100.0  | 30D107M040DC2A     | 0.374 x 0.807 [9.5 x 20.5]                  | 2.585  | 0.234   |
| 470.0  | 30D477M040DH2A     | 0.374 x 1.496 [9.5 x 38.0]                  | 0.543  | 0.663   |
| 1000.0   | 30D108M040FK2A     | 0.492 x 1.752 [12.5 x 44.5]                 | 0.258  | 1.210   |
| 2200.0   | 30D228M040LS2A     | 0.709 x 1.575 [18.0 x 40.0]                 | 0.125  | 2.040   |
| <b>50 WV<sub>DC</sub> AT +105 °C, SURGE = 65 V</b> |                    |   |  |   |
| 10.0   | 30D106M050BA2A     | 0.248 x 0.512 [6.3 x 13.0]                  | 25.85  | 0.048   |
| 22.0   | 30D226M050BB2A     | 0.248 x 0.689 [6.3 x 17.5]                  | 11.700   | 0.081   |
| 33.0   | 30D336M050CB2A     | 0.315 x 0.689 [8.0 x 17.5]                  | 7.850  | 0.112   |
| 100.0  | 30D107M050DC2A     | 0.374 x 0.807 [9.5 x 20.5]                  | 2.585  | 0.233   |
| 220.0  | 30D227M050DF2A     | 0.374 x 1.260 [9.5 x 32.0]                  | 1.177  | 0.417   |
| 330.0  | 30D337M050DH2A     | 0.374 x 1.496 [9.5 x 38.0]                  | 0.785  | 0.551   |
| 1500.0   | 30D158M050GK2A     | 0.630 x 1.752 [16.0 x 44.5]                 | 0.176  | 1.670   |
| <b>63 WV<sub>DC</sub> AT +105 °C, SURGE = 75 V</b> |                    |   |  |   |
| 15.0   | 30D156M063BB2A     | 0.248 x 0.689 [6.3 x 17.5]                  | 16.580   | 0.068   |
| 33.0   | 30D336M063CB2A     | 0.315 x 0.689 [8.0 x 17.5]                  | 7.370  | 0.116   |
| 47.0   | 30D476M063CC2A     | 0.315 x 0.807 [8.0 x 20.5]                  | 5.100  | 0.149   |
| 100.0  | 30D107M063DD2A     | 0.374 x 0.945 [9.5 x 24.0]                  | 2.426  | 0.256   |
| 220.0  | 30D227M063EF2A     | 0.433 x 1.260 [11.0 x 32.0]                 | 1.105  | 0.467   |
| 470.0  | 30D477M063EH2A     | 0.433 x 1.496 [11.0 x 38.0]                 | 0.510  | 0.745   |
| 1000.0   | 30D108M063GK2A     | 0.630 x 1.752 [16.0 x 44.5]                 | 0.242  | 1.420   |



| <b>ELECTRICAL DATA AND ORDERING INFORMATION</b>      |                    |   |  |   |
|--|--------------------|---|--|---|
| <b>CAPACITANCE<br/>(<math>\mu</math>F)</b>           | <b>PART NUMBER</b> | <b>NOMINAL CASE SIZE<br/>D x L<br/>[mm]</b> | <b>MAX. ESR<br/>AT +25 °C<br/>120 Hz<br/>(<math>\Omega</math>)</b> | <b>MAX. RIPPLE<br/>AT +85 °C<br/>120 Hz<br/>(A)</b> |
| <b>75 WV<sub>DC</sub> AT +105 °C, SURGE = 85 V</b>   |                    |   |  |   |
| 12.0   | 30D126M075BB2A     | 0.248 x 0.689 [6.3 x 17.5]                  | 13.200   | 0.076   |
| 47.0   | 30D476M075DC2A     | 0.374 x 0.807 [9.5 x 20.5]                  | 3.384  | 0.204   |
| 120.0  | 30D127M075DF2A     | 0.374 x 1.260 [9.5 x 32.0]                  | 1.320  | 0.392   |
| 1000.0   | 30D108M075LS2A     | 0.709 x 1.575 [18.0 x 40.0]                 | 0.160  | 1.810   |
| <b>100 WV<sub>DC</sub> AT +105 °C, SURGE = 125 V</b> |                    |   |  |   |
| 4.7  | 30D475M100BB2A     | 0.248 x 0.689 [6.3 x 17.5]                  | 33.840   | 0.048   |
| 10.0   | 30D106M100CB2A     | 0.315 x 0.689 [8.0 x 17.5]                  | 16.097   | 0.079   |
| 100.0  | 30D107M100DH2A     | 0.374 x 1.496 [9.5 x 38.0]                  | 1.609  | 0.386   |
| 220.0  | 30D227M100EK2A     | 0.492 x 1.752 [12.5 x 44.5]                 | 0.733  | 0.717   |
| 470.0  | 30D477M100LS2A     | 0.709 x 1.575 [18.0 x 40.0]                 | 0.338  | 1.240   |
| <b>160 WV<sub>DC</sub> AT +105 °C, SURGE = 180 V</b> |                    |   |  |   |
| 1.5  | 30D155M160BA2A     | 0.248 x 0.512 [6.3 x 13.0]                  | 110.10   | 0.023   |
| 3.3  | 30D335M160CB2A     | 0.315 x 0.689 [8.0 x 17.5]                  | 48.880   | 0.045   |
| 10.0   | 30D106M160DC2A     | 0.374 x 0.807 [9.5 x 20.5]                  | 16.097   | 0.093   |
| 22.0   | 30D226M160DF2A     | 0.374 x 1.260 [9.5 x 32.0]                  | 7.333  | 0.166   |
| 33.0   | 30D336M160EF2A     | 0.433 x 1.260 [11.0 x 32.0]                 | 4.888  | 0.222   |
| 47.0   | 30D476M160EH2A     | 0.433 x 1.496 [11.0 x 38.0]                 | 3.384  | 0.289   |
| 100.0  | 30D107M160GK2A     | 0.630 x 1.752 [16.0 x 44.5]                 | 1.609  | 0.552   |
| <b>200 WV<sub>DC</sub> AT +105 °C, SURGE = 250 V</b> |                    |   |  |   |
| 1.2  | 30D125M200BA2A     | 0.248 x 0.512 [6.3 x 13.0]                  | 132.01   | 0.022   |
| 4.7  | 30D475M200CC2A     | 0.315 x 0.807 [8.0 x 20.5]                  | 33.850   | 0.058   |
| 8.2  | 30D825M200DC2A     | 0.374 x 0.807 [9.5 x 20.5]                  | 19.410   | 0.085   |
| 10.0   | 30D106M200DD2A     | 0.374 x 0.945 [9.5 x 24.0]                  | 16.090   | 0.101   |
| 22.0   | 30D226M200DH2A     | 0.374 x 1.496 [9.5 x 38.0]                  | 7.331  | 0.181   |
| 33.0   | 30D336M200EH2A     | 0.433 x 1.496 [11.0 x 38.0]                 | 4.880  | 0.241   |
| 47.0   | 30D476M200EK2A     | 0.492 x 1.752 [12.5 x 44.5]                 | 3.384  | 0.334   |
| 100.0  | 30D107M200LS2A     | 0.709 x 1.575 [18.0 x 40.0]                 | 1.609  | 0.571   |
| <b>250 WV<sub>DC</sub> AT +105 °C, SURGE = 300 V</b> |                    |   |  |   |
| 1.0  | 30D105M250BA2A     | 0.248 x 0.512 [6.3 x 13.0]                  | 160.97   | 0.021   |
| 3.3  | 30D335M250CC2A     | 0.315 x 0.807 [8.0 x 20.5]                  | 48.010   | 0.049   |
| 12.0   | 30D126M250DF2A     | 0.374 x 1.260 [9.5 x 32.0]                  | 13.210   | 0.124   |
| 47.0   | 30D476M250GH2A     | 0.630 x 1.496 [16.0 x 38.0]                 | 3.384  | 0.355   |

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.