## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



			REVISIONS			
ASSY PN: 310J100 -	-CA		LTR	DESCRIPTION	DATE	APPROVAL
			NC INITIAL RELEASE		10-04-10	JRP
	NUMBER OF CONDUCTO CONNECTOR PN: 71600- ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ORS 0_XXLF	<sup>T</sup> H (FEET):CA003;CA006;C ER OF CONDUCTORS	CA012		
		(A) BILL OF MATERIALS				
		QTY	DESC	PN	M	FG
		2	CONNECTOR, IDC	71600-0XXLF*	FCI	
NOTES: 1) INSTALL IDC CONNECTORS AS REQUIRED. 2 USE 310J101 CABLE. 3) THE ID OF THIS ASSY IS PRODUCTION PREFERENCE. 4) STRIP AND TIN PER IEC-J-STD-001. 5) ULTRA FLEXIBLE, FINELY STRANDED COPPER			NO CICOIL PN, REV	SUPPLIER PN, REV DE	SCRIPTION	στγ
6) INTERMEDIATE FLEX: 6X CABLE HEIGHT		VIEW PRC		<u>uuluuluuluuluuluuluuluuluu</u> DATE	CICOIL	
<ul> <li>7) CONTINUOUS FLEX: 10X CABLE HEIGHT</li> <li>8) OUTER JACKET DUROMETER RATING: 65 (SHORE A)</li> <li>9) ASSEMBLY TEMPERATURE RATING: -65 ℃ TO +105° CABLE TEMPERATURE RATING: -65 ℃ TO +260 ℃</li> <li>10) OUTER JACKET DIELECTRIC STRENGTH: 450 VOLTS/MIL (17.7)</li> <li>11) *OR EQUIVALENT</li> </ul>	kv/mm)	UNLESS OTHERN DIMENSIONS AFE IN INC .X± .XX± .XX± .005 FRAC± ANGLES± 	HES DRAWN JRP CHECK JRP	100410 TITLE STANDARE DRAWING, CAGE CODE SIZ	VALENCIA, CALIFORNIA PRODUCT DEFIN RIBBON CABLE, ( PROVING NUMBER	(IDC)
	DASH QTY NEXT FINAL NO REQD ASSEMBLY ASSEMB	LY	APPR.		A \$10J100-XX-CAX	
	APPLICATION	DO NOT SCALE D	RAWING	SCALE: NONE 316J	100-XX-CAXXX	EI-OF