



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# AI...

## Ferrules With Insulating Collar According to DIN 46228-4



### CLIPLINE

Data Sheet  
103090s\_en\_01

© PHOENIX CONTACT 2011-07-05

## 1 Description

A special feature of **AI...** ferrules with insulating collar is that the closer the connections are, the more reliable the insulation is and the less likely the wires are to splice. The dimensions of the ferrules correspond to DIN 46228-4.

The metal insulating sleeve is made from a soft electrolytic copper (E-CU) with tin plating, which ensures optimum connection when crimped with the appropriate Phoenix Contact tools.

The insulating collar made from polypropylene, which is resistant to extreme heat, insulates and simplifies fitting onto the wire without having to splice the individual litz wires. The cross section sizes are color coded. They are listed according to DIN 46228-4, Weidmüller standard, and French standard NF C 63-023.



Make sure you always use the latest documentation.  
It can be downloaded at [www.phoenixcontact.net/catalog](http://www.phoenixcontact.net/catalog).



This data sheet is valid for all products listed on the following page:

## 2 Dimensions and Ordering Data

### Ferrules With Insulating Collar According to DIN 46228-4

| Cross Section        | l <sub>1</sub> | l <sub>2</sub> | d <sub>1</sub> | s <sub>1</sub> | d <sub>2</sub> | s <sub>2</sub> | Color     | Color Code <sup>1</sup> | Type                             | Order No. | Pcs./Pck. |
|----------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------|-------------------------|----------------------------------|-----------|-----------|
| 0.14 mm <sup>2</sup> | 12.5 mm        | 8.0 mm         | 0.8 mm         | 0.15 mm        | 1.8 mm         | 0.25 mm        | Gray      | –                       | AI 0,14- 8 GY -1000 <sup>2</sup> | 3203011   | 1000      |
| 0.25 mm <sup>2</sup> | 10.5 mm        | 6.0 mm         | 0.8 mm         | 0.15 mm        | 1.8 mm         | 0.25 mm        | Blue      | –                       | AI 0,25- 6 BU <sup>2</sup>       | 3203040   | 100       |
| 0.25 mm <sup>2</sup> | 10.5 mm        | 6.0 mm         | 0.8 mm         | 0.15 mm        | 1.8 mm         | 0.25 mm        | Yellow    | –                       | AI 0,25- 6 YE <sup>2</sup>       | 3203024   | 100       |
| 0.25 mm <sup>2</sup> | 12.5 mm        | 8.0 mm         | 0.8 mm         | 0.15 mm        | 1.8 mm         | 0.25 mm        | Yellow    | –                       | AI 0,25- 8 YE <sup>2</sup>       | 3203037   | 100       |
| 0.34 mm <sup>2</sup> | 10.5 mm        | 6.0 mm         | 0.8 mm         | 0.15 mm        | 1.8 mm         | 0.25 mm        | Turquoise | –                       | AI 0,34-6 TQ <sup>2</sup>        | 3203053   | 100       |
| 0.34 mm <sup>2</sup> | 10.5 mm        | 8.0 mm         | 0.8 mm         | 0.15 mm        | 1.8 mm         | 0.25 mm        | Turquoise | –                       | AI 0,34-8 TQ <sup>2</sup>        | 3203066   | 100       |
| 0.5 mm <sup>2</sup>  | 12.0 mm        | 6.0 mm         | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | Orange    | W                       | AI 0,5 - 6 OG                    | 3201301   | 100       |
| 0.5 mm <sup>2</sup>  | 12.0 mm        | 6.0 mm         | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | White     | DIN/NF                  | AI 0,5 - 6 WH                    | 3200687   | 100       |
| 0.5 mm <sup>2</sup>  | 14.0 mm        | 8.0 mm         | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | Orange    | W                       | AI 0,5 - 8 OG                    | 3201123   | 100       |
| 0.5 mm <sup>2</sup>  | 14.0 mm        | 8.0 mm         | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | Orange    | W                       | AI 0,5 - 8 OG-1000               | 3202902   | 1000      |
| 0.5 mm <sup>2</sup>  | 14.0 mm        | 8.0 mm         | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | White     | DIN/NF                  | AI 0,5 - 8 WH                    | 3200014   | 100       |
| 0.5 mm <sup>2</sup>  | 14.0 mm        | 8.0 mm         | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | White     | DIN/NF                  | AI 0,5 - 8 WH -1000              | 3200881   | 1000      |
| 0.5 mm <sup>2</sup>  | 16.0 mm        | 10.0 mm        | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | White     | DIN/NF                  | AI 0,5 -10 WH                    | 3201275   | 100       |
| 0.5 mm <sup>2</sup>  | 16.0 mm        | 10.0 mm        | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | White     | DIN/NF                  | AI 0,5 -10 WH-1000               | 3203105   | 1000      |
| 0.5 mm <sup>2</sup>  | 18.0 mm        | 12.0 mm        | 1.1 mm         | 0.15 mm        | 2.5 mm         | 0.3 mm         | White     | DIN/NF                  | AI 0,5 -12 WH <sup>2</sup>       | 3200506   | 100       |
| 0.75 mm <sup>2</sup> | 12.0 mm        | 6.0 mm         | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | Gray      | DIN                     | AI 0,75- 6 GY                    | 3200690   | 100       |
| 0.75 mm <sup>2</sup> | 12.0 mm        | 6.0 mm         | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | White     | W                       | AI 0,75- 6 WH                    | 3201314   | 100       |
| 0.75 mm <sup>2</sup> | 14.0 mm        | 8.0 mm         | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | Blue      | NF                      | AI 0,75- 8 BU                    | 3200027   | 100       |
| 0.75 mm <sup>2</sup> | 14.0 mm        | 8.0 mm         | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | Gray      | DIN                     | AI 0,75- 8 GY                    | 3200519   | 100       |
| 0.75 mm <sup>2</sup> | 14.0 mm        | 8.0 mm         | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | Gray      | DIN                     | AI 0,75- 8 GY -1000              | 3200894   | 1000      |
| 0.75 mm <sup>2</sup> | 14.0 mm        | 8.0 mm         | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | White     | W                       | AI 0,75- 8 WH                    | 3201110   | 100       |
| 0.75 mm <sup>2</sup> | 16.0 mm        | 10.0 mm        | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | Gray      | DIN                     | AI 0,75-10 GY                    | 3201288   | 100       |
| 0.75 mm <sup>2</sup> | 16.0 mm        | 10.0 mm        | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | Gray      | DIN                     | AI 0,75-10 GY-1000               | 3203118   | 1000      |
| 0.75 mm <sup>2</sup> | 18.0 mm        | 12.0 mm        | 1.3 mm         | 0.15 mm        | 2.8 mm         | 0.3 mm         | Gray      | DIN                     | AI 0,75-12 GY                    | 3200849   | 100       |
| 1 mm <sup>2</sup>    | 12.5 mm        | 6.0 mm         | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Red       | DIN/NF                  | AI 1 - 6 RD                      | 3200742   | 100       |
| 1 mm <sup>2</sup>    | 12.5 mm        | 6.0 mm         | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Yellow    | W                       | AI 1 - 6 YE                      | 3201327   | 100       |
| 1 mm <sup>2</sup>    | 14.5 mm        | 8.0 mm         | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Red       | DIN/NF                  | AI 1 - 8 RD                      | 3200030   | 100       |
| 1 mm <sup>2</sup>    | 14.5 mm        | 8.0 mm         | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Red       | DIN/NF                  | AI 1 - 8 RD -1000                | 3200904   | 1000      |
| 1 mm <sup>2</sup>    | 14.5 mm        | 8.0 mm         | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Yellow    | W                       | AI 1 - 8 YE                      | 3201097   | 100       |
| 1 mm <sup>2</sup>    | 14.5 mm        | 8.0 mm         | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Yellow    | W                       | AI 1 - 8 YE-1000                 | 3202915   | 1000      |
| 1 mm <sup>2</sup>    | 16.5 mm        | 10.0 mm        | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Red       | DIN/NF                  | AI 1 -10 RD                      | 3200182   | 100       |
| 1 mm <sup>2</sup>    | 16.5 mm        | 10.0 mm        | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Red       | DIN/NF                  | AI 1 -10 RD-1000                 | 3203121   | 1000      |
| 1 mm <sup>2</sup>    | 18.5 mm        | 12.0 mm        | 1.5 mm         | 0.15 mm        | 3.0 mm         | 0.3 mm         | Red       | DIN/NF                  | AI 1 -12 RD                      | 3200674   | 100       |
| 1.5 mm <sup>2</sup>  | 12.5 mm        | 6.0 mm         | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Black     | DIN/NF                  | AI 1,5 - 6 BK <sup>2</sup>       | 3200755   | 100       |
| 1.5 mm <sup>2</sup>  | 14.5 mm        | 8.0 mm         | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Black     | DIN/NF                  | AI 1,5 - 8 BK                    | 3200043   | 100       |
| 1.5 mm <sup>2</sup>  | 14.5 mm        | 8.0 mm         | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Black     | DIN/NF                  | AI 1,5 - 8 BK -1000              | 3200917   | 1000      |
| 1.5 mm <sup>2</sup>  | 14.5 mm        | 8.0 mm         | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Red       | W                       | AI 1,5 - 8 RD                    | 3201136   | 100       |
| 1.5 mm <sup>2</sup>  | 14.5 mm        | 8.0 mm         | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Red       | W                       | AI 1,5 - 8 RD-1000               | 3202928   | 1000      |
| 1.5 mm <sup>2</sup>  | 16.5 mm        | 10.0 mm        | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Black     | DIN/NF                  | AI 1,5 -10 BK                    | 3200195   | 100       |
| 1.5 mm <sup>2</sup>  | 16.5 mm        | 10.0 mm        | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Black     | DIN/NF                  | AI 1,5 -10 BK-1000               | 3203134   | 1000      |
| 1.5 mm <sup>2</sup>  | 18.5 mm        | 12.0 mm        | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Black     | DIN/NF                  | AI 1,5 -12 BK                    | 3201482   | 100       |
| 1.5 mm <sup>2</sup>  | 24.5 mm        | 18.0 mm        | 1.8 mm         | 0.15 mm        | 3.4 mm         | 0.3 mm         | Black     | DIN/NF                  | AI 1,5 -18 BK                    | 3200056   | 100       |
| 2.5 mm <sup>2</sup>  | 15.0 mm        | 8.0 mm         | 2.3 mm         | 0.15 mm        | 4.2 mm         | 0.3 mm         | Blue      | DIN/W                   | AI 2,5 - 8 BU                    | 3200522   | 100       |
| 2.5 mm <sup>2</sup>  | 15.0 mm        | 8.0 mm         | 2.3 mm         | 0.15 mm        | 4.2 mm         | 0.3 mm         | Blue      | DIN/W                   | AI 2,5 - 8 BU -1000              | 3200920   | 1000      |
| 2.5 mm <sup>2</sup>  | 15.0 mm        | 8.0 mm         | 2.3 mm         | 0.15 mm        | 4.2 mm         | 0.3 mm         | Gray      | NF                      | AI 2,5 - 8 GY                    | 3200069   | 100       |
| 2.5 mm <sup>2</sup>  | 17.0 mm        | 10.0 mm        | 2.3 mm         | 0.15 mm        | 4.2 mm         | 0.3 mm         | Blue      | DIN/W                   | AI 2,5 -10 BU <sup>2</sup>       | 3202533   | 100       |
| 2.5 mm <sup>2</sup>  | 17.0 mm        | 10.0 mm        | 2.3 mm         | 0.15 mm        | 4.2 mm         | 0.3 mm         | Blue      | DIN/W                   | AI 2,5 -10 BU-1000 <sup>2</sup>  | 3203147   | 1000      |
| 2.5 mm <sup>2</sup>  | 19.0 mm        | 12.0 mm        | 2.3 mm         | 0.15 mm        | 4.2 mm         | 0.3 mm         | Blue      | DIN/W                   | AI 2,5 -12 BU                    | 3200962   | 100       |
| 2.5 mm <sup>2</sup>  | 19.0 mm        | 12.0 mm        | 2.3 mm         | 0.15 mm        | 4.2 mm         | 0.3 mm         | Gray      | NF                      | AI 2,5 -12 GY                    | 3200205   | 100       |

## Ferrules With Insulating Collar According to DIN 46228-4 [...]

| Cross Section       | $l_1$   | $l_2$   | $d_1$   | $s_1$   | $d_2$   | $s_2$  | Color  | Color Code <sup>1</sup> | Type                       | Order No. | Pcs./Pck. |
|---------------------|---------|---------|---------|---------|---------|--------|--------|-------------------------|----------------------------|-----------|-----------|
| 2.5 mm <sup>2</sup> | 25.0 mm | 18.0 mm | 2.3 mm  | 0.15 mm | 4.2 mm  | 0.3 mm | Blue   | DIN/W                   | AI 2,5 -18 BU              | 3200580   | 100       |
| 2.5 mm <sup>2</sup> | 25.0 mm | 18.0 mm | 2.3 mm  | 0.15 mm | 4.2 mm  | 0.3 mm | Gray   | NF                      | AI 2,5 -18 GY              | 3200072   | 100       |
| 4 mm <sup>2</sup>   | 17.5 mm | 10.0 mm | 2.9 mm  | 0.2 mm  | 4.7 mm  | 0.3 mm | Gray   | DIN/W                   | AI 4 -10 GY                | 3200535   | 100       |
| 4 mm <sup>2</sup>   | 17.5 mm | 10.0 mm | 2.9 mm  | 0.2 mm  | 4.7 mm  | 0.3 mm | Orange | NF                      | AI 4 -10 OG                | 3200085   | 100       |
| 4 mm <sup>2</sup>   | 19.5 mm | 12.0 mm | 2.9 mm  | 0.2 mm  | 4.7 mm  | 0.3 mm | Gray   | DIN/W                   | AI 4 -12 GY                | 3200959   | 100       |
| 4 mm <sup>2</sup>   | 19.5 mm | 12.0 mm | 2.9 mm  | 0.2 mm  | 4.7 mm  | 0.3 mm | Orange | NF                      | AI 4 -12 OG                | 3200438   | 100       |
| 4 mm <sup>2</sup>   | 22.5 mm | 18.0 mm | 2.9 mm  | 0.2 mm  | 4.7 mm  | 0.3 mm | Gray   | DIN/W                   | AI 4 -18 GY                | 3200593   | 100       |
| 4 mm <sup>2</sup>   | 22.5 mm | 18.0 mm | 2.9 mm  | 0.2 mm  | 4.7 mm  | 0.3 mm | Orange | NF                      | AI 4 -18 OG                | 3200098   | 100       |
| 6 mm <sup>2</sup>   | 20.0 mm | 12.0 mm | 3.6 mm  | 0.2 mm  | 6.2 mm  | 0.3 mm | Black  | W                       | AI 6 -12 BK                | 3201107   | 100       |
| 6 mm <sup>2</sup>   | 20.0 mm | 12.0 mm | 3.6 mm  | 0.2 mm  | 6.2 mm  | 0.3 mm | Green  | NF                      | AI 6 -12 GN                | 3200108   | 100       |
| 6 mm <sup>2</sup>   | 20.0 mm | 12.0 mm | 3.6 mm  | 0.2 mm  | 6.2 mm  | 0.3 mm | Yellow | DIN                     | AI 6 -12 YE                | 3200548   | 100       |
| 6 mm <sup>2</sup>   | 26.0 mm | 18.0 mm | 3.6 mm  | 0.2 mm  | 6.2 mm  | 0.3 mm | Green  | NF                      | AI 6 -18 GN                | 3200111   | 100       |
| 6 mm <sup>2</sup>   | 26.0 mm | 18.0 mm | 3.6 mm  | 0.2 mm  | 6.2 mm  | 0.3 mm | Yellow | DIN                     | AI 6 -18 YE                | 3200603   | 100       |
| 10 mm <sup>2</sup>  | 21.0 mm | 12.0 mm | 4.6 mm  | 0.2 mm  | 7.5 mm  | 0.3 mm | Brown  | NF                      | AI 10 -12 BN               | 3200124   | 100       |
| 10 mm <sup>2</sup>  | 21.0 mm | 12.0 mm | 4.6 mm  | 0.2 mm  | 7.5 mm  | 0.3 mm | Ivory  | W                       | AI 10 -12 IV               | 3201068   | 100       |
| 10 mm <sup>2</sup>  | 21.0 mm | 12.0 mm | 4.6 mm  | 0.2 mm  | 7.5 mm  | 0.3 mm | Red    | DIN                     | AI 10 -12 RD               | 3200551   | 100       |
| 10 mm <sup>2</sup>  | 27.0 mm | 18.0 mm | 4.6 mm  | 0.2 mm  | 7.5 mm  | 0.3 mm | Brown  | NF                      | AI 10 -18 BN               | 3200137   | 100       |
| 10 mm <sup>2</sup>  | 27.0 mm | 18.0 mm | 4.6 mm  | 0.2 mm  | 7.5 mm  | 0.3 mm | Red    | DIN                     | AI 10 -18 RD               | 3200616   | 100       |
| 16 mm <sup>2</sup>  | 23.0 mm | 12.0 mm | 6.0 mm  | 0.2 mm  | 8.7 mm  | 0.5 mm | Blue   | DIN                     | AI 16 -12 BU               | 3200564   | 100       |
| 16 mm <sup>2</sup>  | 23.0 mm | 12.0 mm | 6.0 mm  | 0.2 mm  | 8.7 mm  | 0.5 mm | Green  | W                       | AI 16 -12 GN               | 3201152   | 100       |
| 16 mm <sup>2</sup>  | 23.0 mm | 12.0 mm | 6.0 mm  | 0.2 mm  | 8.7 mm  | 0.5 mm | Ivory  | NF                      | AI 16 -12 IV               | 3201181   | 100       |
| 16 mm <sup>2</sup>  | 23.0 mm | 12.0 mm | 6.0 mm  | 0.2 mm  | 8.7 mm  | 0.5 mm | White  | -                       | AI 16 -12 WH               | 3200140   | 100       |
| 16 mm <sup>2</sup>  | 29.0 mm | 18.0 mm | 6.0 mm  | 0.2 mm  | 8.7 mm  | 0.5 mm | Blue   | DIN                     | AI 16 -18 BU               | 3200629   | 100       |
| 16 mm <sup>2</sup>  | 29.0 mm | 18.0 mm | 6.0 mm  | 0.2 mm  | 8.7 mm  | 0.5 mm | Green  | W                       | AI 16 -18 GN               | 3201330   | 100       |
| 16 mm <sup>2</sup>  | 29.0 mm | 18.0 mm | 6.0 mm  | 0.2 mm  | 8.7 mm  | 0.5 mm | White  | -                       | AI 16 -18 WH               | 3200153   | 100       |
| 25 mm <sup>2</sup>  | 29.0 mm | 16.0 mm | 7.5 mm  | 0.2 mm  | 10.8 mm | 0.5 mm | Black  | NF                      | AI 25 -16 BK               | 3200412   | 50        |
| 25 mm <sup>2</sup>  | 29.0 mm | 16.0 mm | 7.5 mm  | 0.2 mm  | 10.8 mm | 0.5 mm | Brown  | W                       | AI 25 -16 BN               | 3201084   | 100       |
| 25 mm <sup>2</sup>  | 29.0 mm | 16.0 mm | 7.5 mm  | 0.2 mm  | 10.8 mm | 0.5 mm | Yellow | DIN                     | AI 25 -16 YE               | 3200577   | 50        |
| 25 mm <sup>2</sup>  | 31.0 mm | 18.0 mm | 7.5 mm  | 0.2 mm  | 10.8 mm | 0.5 mm | Yellow | DIN                     | AI 25 -18 YE               | 3201505   | 50        |
| 25 mm <sup>2</sup>  | 35.0 mm | 22.0 mm | 7.5 mm  | 0.2 mm  | 10.8 mm | 0.5 mm | Black  | NF                      | AI 25 -22 BK               | 3200739   | 50        |
| 25 mm <sup>2</sup>  | 35.0 mm | 22.0 mm | 7.5 mm  | 0.2 mm  | 10.8 mm | 0.5 mm | Yellow | DIN                     | AI 25 -22 YE               | 3200700   | 50        |
| 35 mm <sup>2</sup>  | 30.0 mm | 16.0 mm | 8.5 mm  | 0.2 mm  | 12.3 mm | 0.6 mm | Beige  | W                       | AI 35 -16 BE               | 3201071   | 50        |
| 35 mm <sup>2</sup>  | 30.0 mm | 16.0 mm | 8.5 mm  | 0.2 mm  | 12.3 mm | 0.6 mm | Red    | DIN/NF                  | AI 35 -16 RD               | 3200441   | 50        |
| 35 mm <sup>2</sup>  | 32.0 mm | 18.0 mm | 8.5 mm  | 0.2 mm  | 12.3 mm | 0.6 mm | Red    | DIN/NF                  | AI 35 -18 RD               | 3201495   | 50        |
| 35 mm <sup>2</sup>  | 39.0 mm | 25.0 mm | 8.5 mm  | 0.2 mm  | 12.3 mm | 0.6 mm | Red    | DIN/NF                  | AI 35 -25 RD               | 3200713   | 50        |
| 50 mm <sup>2</sup>  | 36.0 mm | 20.0 mm | 10.5 mm | 0.3 mm  | 15.0 mm | 0.6 mm | Blue   | DIN/NF                  | AI 50 -20 BU               | 3200454   | 50        |
| 50 mm <sup>2</sup>  | 36.0 mm | 20.0 mm | 10.5 mm | 0.3 mm  | 15.0 mm | 0.6 mm | Olive  | W                       | AI 50 -20 OL               | 3201178   | 50        |
| 50 mm <sup>2</sup>  | 41.0 mm | 25.0 mm | 10.5 mm | 0.3 mm  | 15.0 mm | 0.6 mm | Blue   | DIN/NF                  | AI 50 -25 BU               | 3200726   | 25        |
| 50 mm <sup>2</sup>  | 41.0 mm | 25.0 mm | 10.5 mm | 0.3 mm  | 15.0 mm | 0.6 mm | Black  | -                       | AI 50 -25 BK               | 3240678   | 25        |
| 70 mm <sup>2</sup>  | 37.0 mm | 20.0 mm | 12.7 mm | 0.4 mm  | 15.8 mm | 0.7 mm | Yellow | DIN                     | AI 70 -20 YE <sup>2</sup>  | 3201848   | 25        |
| 95 mm <sup>2</sup>  | 44.0 mm | 25.0 mm | 14.5 mm | 0.4 mm  | 18.0 mm | 0.6 mm | Red    | DIN                     | AI 95 -25 RD <sup>2</sup>  | 3201853   | 25        |
| 120 mm <sup>2</sup> | 48.0 mm | 27.0 mm | 16.5 mm | 0.5 mm  | 21.0 mm | 0.7 mm | Blue   | DIN                     | AI 120 -27 BU <sup>2</sup> | 3201822   | 25        |

<sup>1</sup> DIN = Color code according to DIN 46228-4; W = Color code according to Weidmüller standard; NF = Color code according to NF C 63-023

<sup>2</sup> These ferrules are not included in DIN 46228-4.




Figure 1 Dimensions (tolerances according to DIN 46228-4)

- $l_1$  = Total length
- $l_2$  = Sleeve length
- $d_1$  = Inside diameter of sleeve
- $s_1$  = Wall thickness of sleeve
- $d_2$  = Inside diameter of insulating collar
- $s_2$  = Wall thickness of insulating collar

**Assortment Boxes**

| Description   | Type                  | Order No. | Pcs./Pck. |
|---|-----------------------|-----------|-----------|
| Assortment box, red, color coding according to DIN<br>Comprises: 50 pcs. each of AI 0,5-8 WH, AI 2,5-8 BU,<br>100 pcs. each of AI 0,75-8 GY, AI 1-8 RD, AI 1,5-8 BK         | AI-TWIN SORTI BOX RD  | 3202960   | 1         |
| Assortment box, anthracite, color coding according to DIN<br>Comprises: 50 pcs. each of AI 4-10 GY, 20 pcs. each of AI 6-12 YE, AI 10-12 RD,<br>10 pcs. each of AI 16-12 BU | AI-TWIN SORTI BOX ANT | 3202973   | 1         |

**3 Technical Data****General Data**

## Material

Collar

Polypropylene PP (UL94 HB), heat resistant up to 105°C

Sleeve

E-CU, tin-plated surface