

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## Connector - C-SCF 1,5/4,8X0,5 - 3240154

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Slip-on sleeve, non-insulated, 0.75 - 1.5 mm², 4.8 x 0.5

#### **Product Features**

- The uninsulated slip-on sleeves and flat plugs are made from electrolytically tin-plated brass
- They round out the product range in terms of connectors



### Key commercial data

Packing unit	11
Minimum order quantity	100 1
Weight per Piece (excluding packing)	0.43 GRM
Custom tariff number	85366990
Country of origin	Germany

### Technical data

### **Dimensions**

Length (b)	15.6 mm
Width (a)	4.8 mm
Material thickness (g)	0.4 mm

#### Ambient conditions

Ambient temperature (operation)	110 °C
---------------------------------	--------

### General

Color	silver
Stripping length	7 mm
Components	Halogen-free
Material	Brass



# Connector - C-SCF 1,5/4,8X0,5 - 3240154

### Classifications

### eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201
eCl@ss 8.0	27400201

### **ETIM**


ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC001052
ETIM 5.0	EC001052


### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

### **Drawings**

### Dimensioned drawing





© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com