# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



#### PHOENIX CONTACT Deutschland GmbH http://www.phoenixcontact.de

### CD 40X40

Order No.: 3240189

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3240189

Cable duct, grau, bestehend aus Ober- und Unterteil, Breite: 40 mm, Höhe: 40 mm, Länge 2000 mm

#### **Commercial data**

GTIN (EAN)	4 046356 459143
sales group	B204
Pack	25 pcs.
Customs tariff	39259020
Catalog page information	Page 102 (NTK-2010)

## 10/08/2008

Product notes

WEEE/RoHS-compliant since:

http://	

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

#### **Technical data**

#### General

Length (b)	2000 mm
Height	40 mm
Width (a)	40 mm
Color	gray
Inflammability class acc. to UL 94	VO







Ambient tem	perature (operation)	-5 °C 60 °C
Material		PVC
Certificates	/ Approvals	
<b>91</b> (		
Certification		CSA, UL, VDE-PZI
	_	
Accessories	S	
Item	Designation	Description
General		
3240286	CD COVER 40	Cover for cable duct, gray, width: 40 mm, length: 2000 mm
3240284	CD WR	Universal wire holding bracket, perforated, for wiring channels
3240498	RVT-PA 4	Plastic body-bound rivet, 4 mm diameter, for a material thickness of 1.5 6 mm
3240499	RVT-PA 6	Plastic body-bound rivet, 6 mm diameter, for a material thickness of 1.5 6 mm
1212478	UNIFOX-RVT P 4	Rivet setting tool, for use with RVT-PA 4 plastic body-bound rivets
1212509	UNIFOX-RVT P 6	Rivet setting tool, for use with RVT-PA 6 plastic body-bound rivets

#### Address

PHOENIX CONTACT Deutschland GmbH Flachsmarktstr. 8 32825 Blomberg,Germany Phone +49 5235 3 12000 Fax +49 5235 3 41200 http://www.phoenixcontact.de



© 2011 Phoenix Contact Technical modifications reserved;