imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Shield connection terminal block - SKS 14-NS35 - 3240217

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Shield connection terminal block, for applying the shield to busbars

Why buy this product

The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm

Second and identification. As such, shield connection clamps of type SKS can be used in the Ex area even without appropriate approval and identification.

- Three different mounting types supported: on NS 35 DIN rails, on busbars or directly on conductive mounting plates
- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm



Key Commercial Data

Packing unit	10 STK	
GTIN	4 046356 458900	
GTIN	4046356458900	

Technical data

General

Number of levels	1
Number of connections	1
Cable diameter	3 mm 14 mm
Color	silver
Open side panel	No

Dimensions

Length	53.2 mm
Width	19 mm
Height	56.8 mm
Height NS 35/7,5	60 mm
Height NS 35/15	67.5 mm

08/18/2018 Page 1 / 2



Shield connection terminal block - SKS 14-NS35 - 3240217

Technical data

Connection data

Connection method	Spring-cage connection
Conductor cross section solid min.	4 mm ²
Conductor cross section solid max.	13.5 mm ²
Conductor cross section flexible min.	4 mm ²
Conductor cross section flexible max.	13.5 mm ²
Conductor cross section AWG min.	10
Conductor cross section AWG max.	6

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Approvals

Approvals

Approvals		
EAC		

Ex Approvals

Approval details

EAC **ERC** 7500651.22.01.00246

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com