# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



### CD-HF 100X80

Order No.: 3240363

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3240363

Wiring channel, gray, halogen-free, consisting of upper and lower part, width: 100 mm, height: 80 mm, length: 2000 mm

#### **Commercial data**

GTIN	(EAN)

	4 046356 508483
Note	Made-to-order
sales group	B204
Pack	6 pcs.
Customs tariff	39259020
Catalog page information	Page 101 (NTK-2010)

#### Product notes

WEEE/RoHS-compliant since: 05/05/2009

#### http://

www.download.phoenixcontact.com Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

#### **Technical data**

### General

Length (b)	2000 mm
Height	80 mm
Width (a)	100 mm
Color	gray
Base element material	ABS-PC





catalog

Extract from the online

046356 508483

Inflammability class acc. to UL 94	V0
Ambient temperature (operation)	-25 °C 90 °C
Components	Halogen-free
Material	PC/ABS

**Certificates / Approvals** 



Certification		CSA, UL, VDE-PZI
Accessories		
Item	Designation	Description
General		
3240284	CD WR	Universal wire holding bracket, perforated, for wiring channels
3240367	CD-HF COVER 100	Cover for wiring channel, gray, halogen-free, width: 100 mm, length: 2000 mm
3240498	RVT-PA 4	Plastic body-bound rivet, 4 mm diameter, for a material thicknes of 1.5 6 mm
3240499	RVT-PA 6	Plastic body-bound rivet, 6 mm diameter, for a material thicknes of 1.5 6 mm
1212478	UNIFOX-RVT P 4	Rivet setting tool, for use with RVT-PA 4 plastic body-bound rive
1212509	UNIFOX-RVT P 6	Rivet setting tool, for use with RVT-PA 6 plastic body-bound rive

#### Address

PHOENIX CONTACT Inc., USA 586 Fulling Mill Road Middletown, PA 17057,USA Phone (800) 888-7388 Fax (717) 944-1625 http://www.phoenixcon.com



© 2011 Phoenix Contact Technical modifications reserved;