

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









### **CD-HF COVER 40**

Order No.: 3240371



http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3240371

Cover for wiring channel, gray, halogen-free, width: 40 mm, length: 2000 mm

Commercial data	
GTIN (EAN)	4 046356 508568
Note	Made-to-order
sales group	B204
Pack	14 pcs.
Customs tariff	39259020
Catalog page information	Page 101 (NTK-2010)

# Product notes WEEE/RoHS-compliant since: 05/05/2009

http://
www.download.phoenixcontact.com
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

# Technical data

### General

Length (b)	2000 mm
Width (a)	40 mm
Color	gray
Base element material	ABS-PC
Inflammability class acc. to UL 94	V0

## CD-HF COVER 40 Order No.: 3240371

http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3240371

Ambient temperature (operation)	-25 °C 90 °C
Components	Halogen-free
Material	PC/ABS

### Address

PHOENIX CONTACT Inc., USA 586 Fulling Mill Road Middletown, PA 17057,USA Phone (800) 888-7388 Fax (717) 944-1625 http://www.phoenixcon.com



© 2011 Phoenix Contact Technical modifications reserved;