



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Blind rivet - RVT-AL/ST 4,8/12 - 3240521

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Blind rivets, Ø 4.8 mm, 12 mm sleeve length, aluminum sleeve, zinc-plated steel pin, flat head, standard version similar to DIN 7337 A

Product Features

- Special rivets are available for fixing RW... and UW... high-current panel feed-through terminal blocks that are specifically designed for terminal blocks
- Compact, ergonomically shaped pliers
- 3 inserts for rivet diameter of 2.4 - 3.2 mm, 4 mm, and 4.8 - 5.0 mm

Key commercial data

Packing unit	1 PCE
Minimum order quantity	500 PCE
GTIN	 4 046356 527521
Custom tariff number	83082000
Country of origin	CHINA

Technical data

Dimensions

Hole diameter	4.9 mm
---------------	--------

General

Color	silver
Material	Aluminum (AlMg 3/3.5)/galvanized steel

Classifications

eCl@ss

eCl@ss 4.0	21043074
eCl@ss 4.1	21043074

Blind rivet - RVT-AL/ST 4,8/12 - 3240521

Classifications

eCl@ss

eCl@ss 5.0	23120402
eCl@ss 5.1	23120402
eCl@ss 6.0	23120402
eCl@ss 7.0	23120402
eCl@ss 8.0	23120402

ETIM

ETIM 3.0	EC002339
ETIM 4.0	EC002339
ETIM 5.0	EC002339

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703