# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Polyamide protective hose, inflammability class V0, UV resistant

Image shows WP-PA HF 13.0 BK version

# Key Commercial Data

| Packing unit                         | 1 STK    |
|--------------------------------------|----------|
| Minimum order quantity               | 50 STK   |
| Weight per Piece (excluding packing) | 1.000 g  |
| Custom tariff number                 | 39173200 |
| Country of origin                    | Germany  |

# Technical data

#### Dimensions

| Inner diameter (f) | 6.50 mm  |
|--------------------|----------|
| Outside diameter   | 10.00 mm |

#### Ambient conditions

| Ambient temperature (operation) | -40 °C 115 °C |
|---------------------------------|---------------|
| Short-term temperature          | 150 °C        |

General

| black                                    |  |
|--|--|
| Helically corrugated plastic hose        |  |
| free from silicone, halogen, and cadmium |  |
| V0                                       |  |
| PA                                       |  |
| 13.00 mm                                 |  |
| 35.00 mm                                 |  |
| Standards and Regulations                |  |
|  |  |

| Resistance to UV radiation | yes           |           |
|----------------------------|---------------|-----------|
|                            | 08/30/2016 Pa | age 1 / 6 |



### Technical data

#### Standards and Regulations

| Halogen-free                           | yes |
|--|-----|
| Connection in acc. with standard       | UL  |
| Flammability rating according to UL 94 | V0  |

# Classifications

#### eCl@ss

| eCl@ss 4.0 | 27141131 |
|------------|----------|
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141131 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27430304 |
| eCl@ss 9.0 | 27430304 |

### ETIM

| ETIM 3.0 | EC000897 |
|----------|----------|
| ETIM 4.0 | EC001177 |
| ETIM 5.0 | EC001177 |

#### UNSPSC

| UNSPSC 6.01   | 30211812 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121411 |

### Approvals

#### Approvals

#### Approvals

UL Recognized / VDE Zeichengenehmigung / LR / DNV

Ex Approvals



### Approvals

#### Approval details

UL Recognized **N** http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

VDE Zeichengenehmigung Attp://www.vde.de

LR http://www.lr.org/en

DNV http://exchange.dnv.com/tari/

#### Accessories

Accessories

Corrugated pipe screw connection

Screw connection - WP-G HF IP66 PG7 BK - 3240888



Cable gland, Pg thread, IP66 protection, straight

Screw connection - WP-G HF IP66 M10 BK - 3240895



Cable gland, metric thread, IP66 protection, straight

Screw connection - WP-G HF IP69K PG7 BK - 3240874



Cable gland, Pg thread, IP68/69k protection, straight



### Accessories

Screw connection - WP-G HF IP69K M10 BK - 3240881



Cable gland, metric thread, IP68/69k protection, straight

Screw connection - WP-GA HF IP66 PG7 BK - 3240916



Cable gland, Pg thread, IP66 protection, angled

Screw connection - WP-GA HF IP66 M10 BK - 3240923



Cable gland, metric thread, IP66 protection, angled

Screw connection - WP-GA HF IP69K PG7 BK - 3240902



Cable gland, Pg thread, IP68/69k protection, angled

Screw connection - WP-GA HF IP69K M10 BK - 3240909



Cable gland, metric thread, IP68/69k protection, angled

08/30/2016 Page 4 / 6



### Accessories

Screw connection - WP-GR HF IP66 PG7 BK - 3240944



Cable gland, Pg thread, IP66 protection, with strain relief

Screw connection - WP-GR HF IP69K PG7 BK - 3240930



Cable gland, Pg thread, IP68/69k protection, with strain relief

#### Mounting material

Hose holder with cover - WP-BASE C PA HF 10,0 BK - 3240958



Hose holder with cover

Hose clamp - WP-BASE HF 9-10 - 3240965



Hose clamps

Protective cap

Transition sleeve from hose to cable - WP-EC TPE HF 10,0 BK - 3240974



End sleeves, transition sleeves, from hose to cable



### Accessories

Cable protection end sleeve - WP-SC PA HF 10,0 BK - 3240981



End sleeves as cable protection

Phoenix Contact 2016  $\ensuremath{\mathbb{C}}$  - all rights reserved http://www.phoenixcontact.com