



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Protective hose - WP-PA HF 15,8 BK - 3240682

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Polyamide protective hose, inflammability class V0, UV resistant

Image shows WP-PA HF 13.0 BK version

### Key Commercial Data

Packing unit	1 M
Minimum order quantity	50 M
Weight per Piece (excluding packing)	1.000 g
Custom tariff number	39173200
Country of origin	Germany

### Technical data

#### Dimensions

Inner diameter (f)	12.00 mm
Outside diameter	15.80 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
Short-term temperature	150 °C

#### General

Color	black
Type	Helically corrugated plastic hose
Components	free from silicone, halogen, and cadmium
Flammability rating according to UL 94	V0
Material	PA
Bending radius, static	35.00 mm
Bending radius, dynamic	55.00 mm

#### Standards and Regulations

Resistance to UV radiation	yes
----------------------------	-----

# Protective hose - WP-PA HF 15,8 BK - 3240682

## Technical data

### Standards and Regulations

Halogen-free	yes
Connection in acc. with standard	UL
Flammability rating according to UL 94	V0

## Classifications

### eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27430304
eCl@ss 9.0	27430304

### ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC001177
ETIM 5.0	EC001177

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

### Approvals

---

#### Approvals

UL Recognized / VDE Zeichengenehmigung / LR / DNV

---


#### Ex Approvals


---

## Protective hose - WP-PA HF 15,8 BK - 3240682

### Approvals

#### Approval details

UL Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

VDE Zeichengenehmigung  <http://www.vde.de>

LR <http://www.lr.org/en>

DNV <http://exchange.dnv.com/tari/>

### Accessories

#### Accessories

##### Corrugated pipe screw connection

Screw connection - WP-G HF IP66 PG11 BK - 3240890



Cable gland, Pg thread, IP66 protection, straight

Screw connection - WP-G HF IP66 M16 BK - 3240897



Cable gland, metric thread, IP66 protection, straight

Screw connection - WP-G HF IP69K PG11 BK - 3240876



Cable gland, Pg thread, IP68/69k protection, straight

## Protective hose - WP-PA HF 15,8 BK - 3240682

### Accessories

---

Screw connection - WP-G HF IP69K M16 BK - 3240883



Cable gland, metric thread, IP68/69k protection, straight

---

Screw connection - WP-GA HF IP66 PG11 BK - 3240918



Cable gland, Pg thread, IP66 protection, angled

---

Screw connection - WP-GA HF IP66 M16 BK - 3240925



Cable gland, metric thread, IP66 protection, angled

---

Screw connection - WP-GA HF IP69K PG11 BK - 3240904



Cable gland, Pg thread, IP68/69k protection, angled

---

Screw connection - WP-GA HF IP69K M16 BK - 3240911



Cable gland, metric thread, IP68/69k protection, angled

---

## Protective hose - WP-PA HF 15,8 BK - 3240682

### Accessories

Screw connection - WP-GR HF IP66 PG11 BK - 3240946



Cable gland, Pg thread, IP66 protection, with strain relief

---

Screw connection - WP-GR HF IP66 M16 BK - 3240953



Cable gland, metric thread, IP66 protection, with strain relief

---

Screw connection - WP-GR HF IP69K PG11 BK - 3240932



Cable gland, Pg thread, IP68/69k protection, with strain relief

---

Screw connection - WP-GR HF IP69K M16 BK - 3240939



Cable gland, metric thread, IP68/69k protection, with strain relief

---

### Mounting material

Hose holder with cover - WP-BASE C PA HF 15,8 BK - 3240960



Hose holder with cover

---

## Protective hose - WP-PA HF 15,8 BK - 3240682

### Accessories

Hose clamp - WP-BASE HF 15,8 - 3240968



Hose clamps

---

Protective hose fixing bracket - WP-BASE A M16 - 3241083



Fixing bracket for protective sleeves, fixed with two screws

---

### Protective cap

Transition sleeve from hose to cable - WP-EC TPE HF 15,8 BK - 3240976



End sleeves, transition sleeves, from hose to cable

---

Cable protection end sleeve - WP-SC PA HF 15,8 BK - 3240983



End sleeves as cable protection

---