



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Protective hose - WP-SPIRAL PU C HF 10 - 3240856

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective hose, spring steel wire with PU coating, highly stranded

The figure shows a version of the article

Key Commercial Data

Packing unit	1 M
Minimum order quantity	10 M
Weight per Piece (excluding packing)	48.0 g
Custom tariff number	39173200
Country of origin	Germany

Technical data

Dimensions

Inner diameter (f)	7.00 mm
Outside diameter	10.00 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Short-term temperature	120 °C

General

Color	blue
Type	Spring steel wire with PU coating
Components	free from silicone, halogen, and cadmium
Flammability rating according to UL 94	V2
Material	PU
Bending radius, static	8.00 mm

Standards and Regulations

Resistance to UV radiation	no
Halogen-free	yes

Protective hose - WP-SPIRAL PU C HF 10 - 3240856

Technical data

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Classifications

eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27430304

ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC001177
ETIM 5.0	EC001177

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Approvals

Approvals

Approvals

VDE Zeichengenehmigung


Ex Approvals

Approvals submitted

Protective hose - WP-SPIRAL PU C HF 10 - 3240856

Approvals

Approval details

VDE Zeichengenehmigung 

Accessories

Accessories

Corrugated pipe screw connection

Screw connection - WP-G PP HF PG7 - 3240988



Cable gland made from PP with Pg thread, IP65 protection

Screw connection - WP-G PP HF M10 - 3240995



Cable gland made from PP with metric thread, IP65 protection

Screw connection - WP-GT PP HF PG7 - 3241002



Cable gland made from PP with Pg thread, rotatable, IP54 protection

Screw connection - WP-GT PP HF M12 - 3241010



Cable gland made from PP with metric thread, rotatable, IP54 protection

Protective hose - WP-SPIRAL PU C HF 10 - 3240856

Accessories

Mounting material

Hose clamp - WP-BASE HF 9-10 - 3240965



Hose clamps

Protective cap

Cable protection end sleeve - WP-SC HF 10 - 3241016



End sleeves as cable protection