



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Transition sleeve from hose to cable - WP-EC TPE HF 13,0 BK - 3240975

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



End sleeves, transition sleeves, from hose to cable

Image shows WP-EC TPE HF 10.0 BK version

### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 STK    |
| Minimum order quantity               | 50 STK   |
| Weight per Piece (excluding packing) | 2.0 g    |
| Custom tariff number                 | 39174000 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                    |          |
|--------------------|----------|
| Length (b)         | 32.5 mm  |
| Inner diameter (f) | 10.00 mm |
| Outside diameter   | 13.00 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
| Short-term temperature          | 150 °C            |

#### General

|  |              |
|--|--------------|
| Color                                  | black        |
| Components                             | Halogen-free |
| Flammability rating according to UL 94 | HB           |
| Material                               | TPE          |

### Standards and Regulations

|  |    |
|--|----|
| Connection in acc. with standard       | UL |
| Flammability rating according to UL 94 | HB |

# Transition sleeve from hose to cable - WP-EC TPE HF 13,0 BK - 3240975

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141131 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27439210 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC002584 |
| ETIM 5.0 | EC000519 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121411 |

## Approvals

### Approvals

---

Approvals

UL Recognized

---

Ex Approvals

---

Approvals submitted

---

### Approval details

|               |
|---------------|
| UL Recognized |
|---------------|

