

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Screw connection - WP-G PP HF PG9 - 3240989

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable gland made from PP with Pg thread, IP65 protection

The figure shows a version of the article

Key Commercial Data

| Packing unit | 1 STK |
|------------------------|----------|
| Minimum order quantity | 10 STK |
| Custom tariff number | 39174000 |
| Country of origin | Germany |

Technical data

Dimensions

| Width (a) | 25 mm |
|------------------|-----------|
| Height | 41 mm |
| Wrench size | 21.00 mm |
| Outside diameter | 14.00 mm |
| Cable diameter | 9 mm 9 mm |

Ambient conditions

| Ambient temperature (operation) | -10 °C 110 °C |
|---------------------------------|---------------|
| Degree of protection | IP65 |

General

| Color | gray |
|--|--------------|
| Туре | Straight |
| | Outer thread |
| Components | Halogen-free |
| Flammability rating according to UL 94 | НВ |
| Material | PP |

Standards and Regulations



Screw connection - WP-G PP HF PG9 - 3240989

Technical data

Standards and Regulations

| Flammability rating according to UL 94 HB |
|---|
|---|

Classifications

eCl@ss

| eCl@ss 4.0 | 27141131 |
|------------|----------|
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141131 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27149109 |
| eCl@ss 9.0 | 27144432 |

ETIM

| ETIM 3.0 | EC000897 |
|----------|----------|
| ETIM 4.0 | EC001178 |
| ETIM 5.0 | EC001178 |

UNSPSC

| UNSPSC 6.01 | 30211812 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121411 |
| UNSPSC 12.01 | 39121411 |
| UNSPSC 13.2 | 39121411 |

Approvals

Approvals

Approvals

VDE Zeichengenehmigung

Ex Approvals

Approvals submitted



Screw connection - WP-G PP HF PG9 - 3240989

Approvals

Approval details

VDE Zeichengenehmigung



Accessories

Accessories

Corrugated pipe

Protective hose - WP-SPIRAL PVC C 14 - 3240850



Protective hose, spring steel wire with PVC coating, highly stranded

Protective hose - WP-SPIRAL PU C HF 14 - 3240857



Protective hose, spring steel wire with PU coating, highly stranded

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com