# mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# Flat gasket - WP-FS HF IP68 M25 - 3241177

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Flat gasket, Height: 1.8 mm, Diameter: 37 mm, Color: green



#### Why buy this product

- The Centellen flat sealing rings are used to seal protective hose screw connections on uneven surfaces.
- IP68 degree of protection
- Resistant to oil, seal against dust and water, UV resistant, halogen-free, high mechanical stability

### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
Custom tariff number	40169300
Country of origin	Germany

## Technical data

#### Dimensions

Height	1.8 mm
Diameter	37 mm
Inner diameter (f)	25 mm

#### Ambient conditions

Ambient temperature (operation)	-50 °C 200 °C
Degree of protection	IP68

#### General

Color	green
Components	free from silicone and halogen
Material	Centellen



# Flat gasket - WP-FS HF IP68 M25 - 3241177

# Classifications

## eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	21132007
eCl@ss 5.1	27141120
eCl@ss 6.0	21132007
eCl@ss 7.0	27439210
eCl@ss 8.0	27439218
eCl@ss 9.0	27430319

#### ETIM

ETIM 3.0	EC000519
ETIM 4.0	EC000519
ETIM 5.0	EC001181

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com