



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





GREENLEE.
A Textron Company

MADE FOR THE TRADE!™



ROPE-9/16 X 300' NYLON/POLYESTER

Double-Braided Composite Rope 9/16 × 300' (14.3 mm × 91 m)

Cat No: 35283

UPC No: 783310352839

Description

- Double-braided inner core with an extra double-braided outer jacket for added strength and less stretch
- white with green tracer
- Rot and mildew resistant
- Factory spliced eyes at both ends
- Lowest stretch
- Select a rope with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force

Specifications

- Application : For The UT4 And 640 Puller
- Average Breaking Strength : 16000.000 LB (71.100 KN)
- Color : White With Green Tracer
- Material : Nylon/Polyester
- Maximum Rated Capacity : 4000.000 LB (17.800 KN)
- Rope Diameter : 9/16 IN (14.300 MM)
- Rope Length : 300.000 FT (91.000 M)
- Rope Stand : 644
- Type : Double Braided
- Weight : 28.000 LB (12.700 KG)