



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SGV SERIES

UPGRADE

105°C Standard

- Load Life : 105°C 2000~5000 hours.
- AEC-Q200.
- High Temperature Reflow soldering is available. (JGV series)
(http://www.rubycon.co.jp/catalog/j_pdfs/aluminum/j_JGV.pdf)



RoHS compliance



SPECIFICATIONS

Items	Characteristics																																						
Category Temperature Range	-55~+105°C	-40~+105°C	-25~+105°C																																				
Rated Voltage Range	6.3~50Vdc	63, 100Vdc	160~450Vdc																																				
Capacitance Tolerance	±20% (20°C, 120Hz)																																						
Leakage Current(MAX)	6.3~100Vdc		160~450Vdc																																				
	I=0.01CV or 3μA whichever is greater. (After 2 minutes application of rated voltage)		I=0.04CV+100μA (1minute) I=0.02CV+25μA (5minutes)																																				
	I=Leakage Current(μA) C=Capacitance(μF) V=Rated Voltage(Vdc)																																						
Dissipation Factor(MAX) (tanδ)	<table border="1"> <tr> <th>Rated Voltage (Vdc)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> <th>160~250</th> <th>400</th> <th>450</th> </tr> <tr> <td>φ4,φ5,φ6.3×6.1</td> <td>0.30</td> <td>0.24</td> <td>0.20</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>φ6.3×8,φ8~φ18</td> <td>0.35</td> <td>0.26</td> <td>0.24</td> <td>0.18</td> <td>0.14</td> <td>0.12</td> <td>0.12</td> <td>0.10</td> <td>0.15</td> <td>0.20</td> <td>-</td> </tr> </table>			Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	100	160~250	400	450	φ4,φ5,φ6.3×6.1	0.30	0.24	0.20	0.16	0.14	0.12	-	-	-	-	-	φ6.3×8,φ8~φ18	0.35	0.26	0.24	0.18	0.14	0.12	0.12	0.10	0.15	0.20	-
	Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	100	160~250	400	450																											
φ4,φ5,φ6.3×6.1	0.30	0.24	0.20	0.16	0.14	0.12	-	-	-	-	-																												
φ6.3×8,φ8~φ18	0.35	0.26	0.24	0.18	0.14	0.12	0.12	0.10	0.15	0.20	-																												
When rated capacitance is over 1000μF, tanδ shall be added 0.02 to the listed value with increase of every 1000μF.																																							
Endurance	After applying rated voltage with rated ripple current for specified time at 105°C, the capacitors shall meet the following requirements.																																						
	Capacitance Change	Within ±25% of the initial value.	Rated Voltage (Vdc)	Life Time (hrs)																																			
	Dissipation Factor	Not more than 200% of the specified value.	6.3~100	2000																																			
	Leakage Current	Not more than the specified value.	160~450	5000																																			
Low Temperature Stability Impedance Ratio(MAX)	<table border="1"> <tr> <th>Rated Voltage (Vdc)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>100</th> <th>160~250</th> <th>400</th> <th>450</th> </tr> <tr> <td>Z(-25°C)/Z(20°C)</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>3</td> <td>6</td> <td>-</td> </tr> <tr> <td>Z(-40°C)/Z(20°C)</td> <td>8</td> <td>8</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> <td>5</td> <td>5</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>			Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	100	160~250	400	450	Z(-25°C)/Z(20°C)	4	3	2	2	2	2	2	2	3	6	-	Z(-40°C)/Z(20°C)	8	8	4	4	3	3	5	5	-	-	-
	Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	100	160~250	400	450																											
Z(-25°C)/Z(20°C)	4	3	2	2	2	2	2	2	3	6	-																												
Z(-40°C)/Z(20°C)	8	8	4	4	3	3	5	5	-	-	-																												
	(120Hz)																																						

MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)	60(50)	120	500	1k	10k≦	
Coefficient	0.47~1μF	0.50	1.00	1.20	1.30	1.50
	2.2~6.8μF	0.65	1.00	1.20	1.30	1.50
	10~68μF	0.80	1.00	1.20	1.30	1.50
	100~1000μF	0.80	1.00	1.10	1.15	1.20
	2200~6800μF	0.80	1.00	1.05	1.10	1.15

PART NUMBER

□□□ / SGV / □□□□□ / M / □□□ / D×L
 Rated Voltage Series Capacitance Capacitance Tolerance Option Case Size

DIMENSIONS

(mm)


φD	L	A1	B1	C	W1	P	K	α
4	6.1	4.3	4.3	1.8	0.5~0.8	1.0	0.5 MAX	0
5	6.1	5.3	5.3	2.2	0.5~0.8	1.3	0.5 MAX	0
6.3	6.1	6.6	6.6	2.7	0.5~0.8	1.8	0.5 MAX	0
6.3	8	6.6	6.6	2.7	0.5~0.8	1.8	0.5 MAX	0
8	6.5	8.3	8.3	3.4	0.5~0.8	2.2	0.5 MAX	0
8	10.5	8.3	8.3	2.9	0.8~1.1	3.1	0.5 MAX	※1
10	10.5	10.3	10.3	3.2	0.8~1.1	4.5	0.5 MAX	※1
12.5	13.5	13	13	4.9	0.8~1.1	4.5	0.7±0.4	0.5
12.5	16	13	13	4.9	0.8~1.1	4.5	0.7±0.4	0.5
16	16.5	17	17	6	1.0~1.6	6.8	0.7±0.4	0.5
16	21.5	17	17	6	1.0~1.6	6.8	0.7±0.4	0.5
18	16.5	19	19	7	1.0~1.6	6.8	0.7±0.4	0.5
18	21.5	19	19	7	1.0~1.6	6.8	0.7±0.4	0.5

※1: α dimensions


Rated Voltage	α
6.3~100	0
160~400	0.2

MARKING

〈φ4~φ10〉



〈φ12.5~φ18〉



※2 Voltage code

Rated Voltage (Vdc)	6.3	10	16	25	35	50	63	100	160	200	250	400	450
Rated Voltage code	0J	1A	1C	1E	1V	1H	1J	2A	2C	2D	2E	2G	2W

◆ STANDARD SIZE

 Size $\phi D \times L$ (mm), Rated Ripple Current (mA r.m.s./105°C, 120Hz)

Vdc	Cap (μ F)	Size ($\phi D \times L$)	Ripple	Vdc	Cap (μ F)	Size ($\phi D \times L$)	Ripple	Vdc	Cap (μ F)	Size ($\phi D \times L$)	Ripple	
6.3	22	4×6.1	26	35	4.7	4×6.1	15	160	12	8×10.5	115	
	33	4×6.1	29		10	5×6.1	28		22	10×10.5	150	
	47	5×6.1	46		22	6.3×6.1	55		39	12.5×13.5	250	
	100	6.3×6.1	71		33	6.3×8	76		47	12.5×16	310	
	220	6.3×8	121				8×6.5		84	68	16×16.5	400
	470	8×10.5	210		100	8×10.5	180		100	18×16.5	480	
	1000	10×10.5	495				10×10.5		305	120	16×21.5	560
		12.5×13.5			220	10×10.5	450		150	18×21.5	690	
	2200	12.5×16	750			330			12.5×16	460	200	10
	3300	16×21.5	930		470	16×16.5	490		15	10×10.5		130
18×16.5		1000		16×21.5	750	33	12.5×13.5	230				
4700	18×21.5		1200	18×16.5		750	47	12.5×16	270			
6800	18×21.5	1350	50	0.47	4×6.1	4	56	16×16.5	350			
10	33	5×6.1		43	1	4×6.1	8	68	18×16.5	440		
	100	6.3×6.1		71	2.2	4×6.1	11	100	16×21.5	500		
	330	8×10.5		195	3.3	4×6.1	14	120	18×21.5	620		
	470	8×10.5		210	4.7	5×6.1	19	250	6.8	8×10.5		85
		10×10.5		440	10	6.3×6.1	35		12	10×10.5		115
	1000	12.5×16		500	22	6.3×8	67		22	12.5×13.5	190	
	2200	16×16.5		810			8×6.5		70	33	12.5×16	240
	3300	16×21.5		1000	33	8×10.5	140		47	16×16.5	320	
		18×16.5			47	8×10.5	167		56	18×16.5	400	
	4700	18×21.5	1200	100		10×10.5	180		68	16×21.5	450	
16	10	4×6.1	28		8×10.5	230	100		18×21.5	560		
	22	5×6.1	39	10×10.5	315	400	2.7		8×10.5	55		
	47	6.3×6.1	70	220	12.5×16		380		4.7	10×10.5	75	
	100	6.3×8	111	330	16×16.5		470	10	12.5×13.5	135		
	220	8×10.5	185	470	16×21.5		550	15	12.5×16	165		
	330	8×10.5	290		18×16.5			1000	18×21.5	22	16×16.5	220
		10×10.5	440	820	27		18×16.5		280			
	470	8×10.5	320	63	22		8×10.5	55	33	16×21.5	320	
		10×10.5	460		33		8×10.5	115	47	18×21.5	400	
	1000	16×16.5	630		47		8×10.5	120	450	6.8	12.5×13.5	110
2200	16×21.5	930	100		12.5×16		225	10		12.5×16	150	
	18×16.5		470		16×16.5	385	15	16×16.5		195		
3300	18×21.5	1150			330	16×21.5	490	18		18×16.5	245	
25	33	6.3×6.1	65		18×16.5	590		22		16×21.5	275	
	47	6.3×8	79		470		18×21.5	345		33	18×21.5	345
		8×6.5	91		100	10	8×10.5	65		450	6.8	12.5×13.5
	100	8×10.5	180			22	10×10.5	90			10	12.5×16
	220	8×10.5	320	33		10×10.5	135	15			16×16.5	195
		10×10.5	355	47		12.5×13.5	160	18			18×16.5	245
	330	10×10.5	450	100		16×16.5	285	22	16×21.5		275	
		12.5×13.5		220		16×21.5	440	33	18×21.5		345	
	470	10×10.5	490			18×16.5		440	450		6.8	12.5×13.5
	1000	16×21.5	700	63		22	8×10.5	55			10	12.5×16
18×16.5		470				47	8×10.5	120			15	16×16.5
2200	18×21.5		1050			100	12.5×16	225			18	18×16.5
3300	18×21.5	1700	220		16×16.5	385	22	16×21.5		275		