## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Item #	O.D. Dimensions	Cell Size - L x W x D	# of Cells
37782	12-9/16" x 4" x 7/16"	14.9mm x 14.55mm x 6.75mm	68
37780	12-9/16" x 4" x 7/16"	29.5mm x 23mm x 6.75mm	27
37784	12-9/16" x 4" x 7/16"	34.65mm x 11.75mm x 6.65mm	36
37781	12-9/16" x 4" x 7/16"	39.6mm x 34.5mm x 6.55mm	14
37783	12-9/16" x 4" x 7/16"	80.75mm x 26.6mm x 6.55mm	10
37785	4-5/16" x 4-5/16" x 5/16"	13mm x 13mm x 8.2mm	25
37786	4-5/16" x 4-5/16" x 5/16"	16.3mm x 13.2mm x 8.2mm	25
37787	4-5/16" x 4-5/16" x 5/16"	20.2mm x 13.1mm x 8.2mm	20
37788	4-5/16" x 4-5/16" x 5/16"	28.3mm x 28.3mm x 8.2mm	5





## **Description:**

Conductive lead chip carriers for ideal for handling, storing, or shipping of small compnents. They are constructed of thermo-formed conductive plastic. The carriers are stackabele to allow for easy storage. Outer shipping boxes are available upon request. The lead chip carriers are Made in America.

Property	Test Method	Value
Specific Gravity	ASTM D-792	1.09
Factor	-	0.03936 lbs/in <sup>3</sup>
Tensile Strength	ASTM D-638	4,200 psi
Tensile Elongation	ASMT D-638	40%
Flexural Modulus	ASTM D-790	220,000 psi
Flexural Strength	ASMT D-790	6,700 psi
Notched Izod	ASTM D-256	5 ft. lbs./in.
H.D.T. @ 66 psi	ASTM D-648	185°F
Total/Free Sulfur	-	<0.15% / <0.004%
Chlorides	-	<0.3 PPM
Outgassing & Corrosivity	-	Low
Bulk Resistivity (Compression Molded)	-	<10E3 ohms-cm
5KV Decay Time	-	<0.01 seconds @ 10% RH
Surface Resistivity (Extruded), Before Formin	- g	5 x 10E4 ohms @0.060" 3 x 10E5 ohms @0.030"

## **Conductive Lead Chip Carriers**

PROTEKTIVE PAK

PROTEKTIVE PAK 13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578, FAX (909) 363-7331 ProtektivePak.com

DRAWING NUMBER 37785 DATE:

March

2008