



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Battery Powered Milliohm Meter

High accuracy, high resolution portable Milliohm Meter
Battery operated for field use

Features:

- Four terminal Kelvin measurements
- Over-temperature and over-voltage protection
- 5 ranges with 100µ max resolution
- Large 2000 count LCD display
- Auto-Hold and Auto power off
- Invalid test indicators prevent inaccurate measurements
- Built-in water resistant case with shoulder strap
- Complete with 8AA batteries, and 2 sets of test leads (4 wire with 4 alligator clips and 4 wire with 2 Kelvin alligator clips)



Kelvin alligator clips

| Specifications | Range | Resolution | Current | Basic Accuracy |
|----------------|--------------------------------------|------------|---------|----------------------|
| Resistance | 200.0m | 0.1m | 100mA | ±(0.5%rdg +2 digits) |
| | 2000m | 1m | 100mA | ±(0.5%rdg +2 digits) |
| | 20.00 | 0.01 | 10mA | ±(0.5%rdg +2 digits) |
| | 200.0 | 0.1 | 10mA | ±(0.5%rdg +2 digits) |
| | 2000 | 1 | 1mA | ±(0.5%rdg +2 digits) |
| Power | 8 AA batteries | | | |
| Dimensions | 9.8 x 7.5 x 4.3" (250 x 190 x 110mm) | | | |
| Weight | 3.3lbs (1.5kg) | | | |

Ordering Information:

- 380580.....Battery Powered Milliohm Meter
 380580-NIST380580 with Calibration Traceable to NIST
 380565.....Test Leads w/Kelvin clips for 380580

