imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Appliance Tester/Power Analyzer

Compact, battery operated device for analyzing AC power loads With PC interface plus datalogging

Features:

- Four simultaneous displays of Watts, Power Factor or VA, Voltage or Hz, Amps
- True RMS Voltage & Current measurements of sine, square, triangular and distorted wave forms with a crest factor < 5
- Max, Data Hold and Overload Protection
- Battery or AC adaptor provides line isolation
- Plug device to be tested directly into the Power Analyzer
- Sampling (update) rate is 2.5 times/second
- Windows[®] 95/98/NT/2000/XP/ME software allows user to download stored data or save data directly, and to create an ASCII file. Computations include phase angle, apparent and reactive power, consumption and cost, and power factor correction
- Complete with Windows compatible software, cable, 8 x AA batteries, power cord, 117 VAC adaptor and case

Applications:

- Measure and Audit power consumption of single phase devices
- Evaluate load performance under varying line conditions
- Demonstrate effectiveness of power conservation efforts
- Characterize device AC power requirements

Model 380803 Datalogger

 Built-in Datalogger stores up to 1,012 readings (Single record storage or continuous datalogging)

Model 380801

Used for data acquisition when connected to a PC

Ordering Information:







Software included to download and store data to a PC

Built-into heavy duty carrying case.

Specifications:	Range	Resolution	Basic Accuracy (%rdg)	Input Signal Range
Watt	200/2000W	0.1/1W	±(0.9% + 4d)@50/60Hz	300V, 20A, 40-400Hz
Power Factor	0.5 to 1.0	0.001	(Based on W, V, A)	250V, 20A, 50/60Hz
Voltage	200.0/750V	0.1/1V	±(0.5%)	750VAC
Current	2/20A via terminals		±(0.5%)	(Fuse Protection)
	2/15A via sockets			
Frequency	40Hz to 20kHz	1Hz to 10Hz	±(0.5%)	
Dimensions/Weight	13.9 x 11.8 x 3.9" (352 x 300 x 100mm) / 3.6 lbs. (1.6 kg)			



www.extech.com