imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Quad Output DC Power Supply

4-in-1 Power Supply

Four power supplies built into one — Two fully adjustable supplies combined with two auxiliary outputs

Features:

- Two 0 to 30V/0 to 5A outputs with selectable Constant Voltage and Constant Current modes
- Outputs up to 60V in series mode or 10A in parallel mode
- Two auxiliary outputs with fixed current of 3 to 6.5V/3A and 8 to 15V/1A
- Overload and short circuit protection
- Complete with power cord and 4 pairs of test leads (banana plug to alligator clip)





Single power supply with multiple DC outputs

Specifications	Range	
Output Voltage (4)	0 to 30V, 0 to 30V, 3 to 6.5V,8 to 15V	
Output Current (4)	0 to 5A, 0 to 5A, 3A (fixed), 1A (fixed)	
Load Voltage Regulation	0.5mV ±3mV	
Line Voltage Regulation	0.1mV ±3mV	
Load Current Regulation	2mA ±5mA	
Line Current Regulation	2mA ±3mA	
Ripple and Noise	<0.5mVrms	
Power	110 to 240VAC, 50/60Hz (Switchable)	
Dimensions	10.2 x 6.3 x 14.5" (260 x 160 x 370mm)	
Weight	26.5lbs (12kg)	

Ordering Information:

382270Quad Output DC Power Supply