



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Loctite Electronics

Henkel-Loctite Corporation
15051 E. Don Julian Rd.
Industry, Ca 91746

Phone 626.968.6511
Fax 626.336.0526

Shelf life and Storage of Multicore Brand Cored Solder Wire

The Mulicore brand of cored solder wire is very stable. There is not an established shelf life. Henkel-Loctite recommends as a good guideline the material be used within 5 years of date of purchase. The performance of the cored wire should not change during and past this time.

The Multicore brand cored solder wire has no special storage conditions. The material is stable over a wide temperature range. Recommended storage conditions 70-85F (20-30C) with 20-50% RH. Exposure to temperature extremes [below 32F (0C) and above 100F (38C)] and high humidity (above 80% RH) should be minimized and may affect performance. Exposure to high heat in excess of 140F (60C) should be avoided.

These guidelines apply to Multicore brand cored solder wire supplied on spools. Once the material is removed from the provided spool, these guideline do not apply. The end user is responsible for evaluating the effectiveness of the material once it has been removed from the spool and stored separately.