



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Flexible Ferrite Sheets



Fair-Rite Products Corp.

The Rigid Solution

Fair-Rite's Flexible Ferrite Sheets provide the benefits of soft-magnetic materials, while freeing you from their mechanical constraints!

These materials are composed of NiZn to provide high-volume resistivity and high insertion-loss over a broad frequency range.

Available in six material grades and four standard thicknesses as thin as 0.13mm, these RoHS compliant sheets come "scored" in a 2mm x 2mm rectangular grid. The recommended operating temperature is -40° to +85°C and the typical thermal conductivity is 6 watt / m-°C. Storage Temperature : -40° to +85°C, suggested shelf life is one year; however shelf life may be extended by storage at 22 – 25°C and 45-55% RH avoiding light and dust.

With its PET backing, it can bend without impacting performance – making it easy to conform and adhere to any surface for improved functionality.

Used primarily for suppressive applications, the amount of noise that is absorbed at higher frequencies is proportional to the resistive component of the permeability ( $\mu''$ ) and the thickness of the ferrite. The operational frequencies can range from below 1 MHz into the GHz range, making it ideal for a multitude of applications.

## **Key Benefits:**

- Can be quickly implemented into custom designs
- Easier to handle in production verse rigid plates
- High surface resistivity
- Can be cut with a knife, razor or scissors Die cutting is available
- Easy to apply – peel and stick

## **Applications:**

- Wireless Power Charging Station
- RFID and NFC antennas
- PCB and IC components
- Switch-mode power supplies

<b>Fair-Rite PN</b>	<b>Material Permeability</b>	<b>Ferrite Thickness</b>	<b>PET Thickness</b>	<b>Tape Thickness</b>	<b>Sheet Size</b>	<b>Total Thickness</b>
38M1010AA1212	20	0.1 mm	0.01 mm	0.02 mm	120 x 120 mm	0.13 mm
38M1020AA1212	20	0.2 mm	0.01 mm	0.02 mm	120 x 120 mm	0.23 mm
38M1040AA0606	20	0.4 mm	0.01 mm	0.02 mm	60 x 60 mm	0.43 mm
38M1050AA0606	20	0.5 mm	0.01 mm	0.02 mm	60 x 60 mm	0.53 mm
38M2010AA1212	<b>45</b>	0.1 mm	0.01 mm	0.02 mm	120 x 120 mm	0.13 mm
38M2020AA1212	<b>45</b>	0.2 mm	0.01 mm	0.02 mm	120 x 120 mm	0.23 mm
38M2040AA0606	<b>45</b>	0.4 mm	0.01 mm	0.02 mm	60 x 60 mm	0.43 mm
38M2050AA0606	<b>45</b>	0.5 mm	0.01 mm	0.02 mm	60 x 60 mm	0.53 mm
38M3010AA1212	60	0.1 mm	0.01 mm	0.02 mm	120 x 120 mm	0.13 mm

38M3020AA1212	60	0.2 mm	0.01 mm	0.02 mm	120 x 120 mm	0.23 mm
38M3040AA0606	60	0.4 mm	0.01 mm	0.02 mm	60 x 60 mm	0.43 mm
38M3050AA0606	60	0.5 mm	0.01 mm	0.02 mm	60 x 60 mm	0.53 mm
38M4010AA1212	<b>120</b>	0.1 mm	0.01 mm	0.02 mm	120 x 120 mm	0.13 mm
38M4020AA1212	<b>120</b>	0.2 mm	0.01 mm	0.02 mm	120 x 120 mm	0.23 mm
38M4040AA0606	<b>120</b>	0.4 mm	0.01 mm	0.02 mm	60 x 60 mm	0.43 mm
38M4050AA0606	<b>120</b>	0.5 mm	0.01 mm	0.02 mm	60 x 60 mm	0.53 mm
38M5010AA1212	140	0.1 mm	0.01 mm	0.02 mm	120 x 120 mm	0.13 mm
38M5020AA1212	140	0.2 mm	0.01 mm	0.02 mm	120 x 120 mm	0.23 mm
38M5040AA0606	140	0.4 mm	0.01 mm	0.02 mm	60 x 60 mm	0.43 mm

38M5050AA0606	140	0.5 mm	0.01 mm	0.02 mm	60 x 60 mm	0.53 mm
38M6010AA1212	<b>220</b>	0.1 mm	0.01 mm	0.02 mm	120 x 120 mm	0.13 mm
38M6020AA1212	<b>220</b>	0.2 mm	0.01 mm	0.02 mm	120 x 120 mm	0.23 mm
38M6040AA0606	<b>220</b>	0.4 mm	0.01 mm	0.02 mm	60 x 60 mm	0.43 mm
38M6050AA0606	<b>220</b>	0.5 mm	0.01 mm	0.02 mm	60 x 60 mm	0.53 mm

